




Verbleibende Rechte vorbehalten. Alle Rechte vorbehalten. In the event of a patent, utility model or design.
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

Die deutsche Version dieser Zeichnung dient nur zur Erleichterung der Handhabung der Handlungen von den englischen Original gilt als verbindlich.
The german version of this drawing has been offered for convenience only and may deviate from the english original.
In case of any deviation the English version shall prevail.



Leiterplatten-Layout für SMT
PCB-Layout for SMT



ohne Ansaughhaube - without hood


Anforderungsstufe 1
performance level 1

Kontaktbereich vergoldet
mating area gold plating


Anschlussbereich verzinkt 4-6 µm
terminal area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
coplanarity area of termination ≤ 0,1 mm

Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
tape on reel packaging according to DIN IEC 60286-3
Verpackungseinheit: 650 Stück
packaging unit: 650 pcs




Abspulrichtung - reel off direction



*Für die Anforderung nach PG 9 der LV214
(Koshiri-Sicherheit)

*For the requirement of the LV214 PG 9
(Koshiri-security)

Dimension no.				Tolerances Dim. for Information ISO 8015		 All Dimensions in mm		Scale 5:1			
Customer drawing: THIS DRAWING IS A CONTROLLED DOCUMENT.				Subject to modification without prior notice. Drawing will not be updated.				ERNI-MiniBridge Male Straight SMT 02p KS*			
								©- 474125-E			
b				01.03.2021				Class SRCP			
Index				Date							