Rittal – The System.

Faster – better – everywhere.





KX 1547.000 E-box KX, carbon steel

State: 11/1/2024 (Source: rittal.com/us-en)



KX 1547.000 - E-box KX, carbon steel

The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.

Features

Model No.	KX 1547.000
Product description	The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.
Material	Housing: Carbon steel
	Door: Carbon steel, all-round foamed-in PU seal
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside,
	textured paint
	Mounting panel: Zinc-plated
Color	RAL 7035
Supply includes	Housing with door
	Mounting panel
	Cam lock with 3 mm double-bit insert
	180° hinge
Protection category NEMA	NEMA 1
	NEMA 3R
	NEMA 4
	NEMA 12
Protection category IP to EN 60 529	IP 66
Type rating according to UL 50E	Type 1
	Type 3R
	Type 4
	Type 12
IK code	IK08

© Rittal 2024 2

Features

Dimensions	Width: 200 mm Height: 400 mm Depth: 80 mm Width: 7.87 " Height: 15.7 " Depth: 3.15 "
Dimensions of mounting plate (W x H)	175 mm x 385 mm 6.89 ″ x 15.2 ″
Material thickness - enclosure	1.25 mm 0.05 ″
Material thickness - door	1.25 mm 0.05 ″
Material thickness – mounting plate	2 mm 0.08 "
Lock	No. of locks: 1
Base material	Carbon steel
Packaging unit	1 pc(s).
Weight/packaging unit	4.15 kg 9.1 lb.
Net weight	3.848
Gross weight	4.153
PCF/PU (cradle-to-gate)	13.7 kg CO2 eq (Cat B)
Note on the PCF class	Category B: PCF value (cradle-to-gate) approximated based on product weight and self-declared
Customs tariff number	94032080
EAN	4028177816497
E-Number Sweden	E3465215
ETIM 8	EC000261
ETIM 7.0	EC000261
ECLASS 8.0	27180101

© Rittal 2024 3

Approvals

Approvals	Bureau Veritas
	DNV-GL
	Lloyds Register of Shipping
	UL + C-UL (listed)
Certificates	Protection category
Explanations	Manufacturer's declaration
	Declaration of conformity
	Declaration of conformity UK

© Rittal 2024 4