#### Power Relay F

TE Internal #: 1-1414168-0

General Purpose Power Relay, DC, Monostable, 1 Form C SPDT-CO, 20 A Contact Rating, 24 VDC Coil Voltage, 24 VDC Contact

Voltage, Power Relay F

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Power Relay

Coil Magnetic System: Monostable

Contact Arrangement: 1 Form C SPDT-CO

Contact Current Class: 30 – 50 A

Current Type: DC

#### **Features**

### **Product Type Features**

Relay & Contactor Type	General Purpose Power Relay
Configuration Features	
Contact Arrangement	1 Form C SPDT-CO
Coil Special Features	Rp 1200Ω
Electrical Characteristics	
Contact Limiting Short-Time Current	240 A
Contact Limiting Continuous Current	60 A
Contact Switching Load (Min)	1000mA @ 5VDC
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Limiting Making Current	120 A
Contact Current Rating	20 A
Coil Voltage Rating	24 VDC
Contact Voltage Rating	24 VDC
Coil Resistance	268 Ω
Contact Limiting Breaking Current	20 A
Coil Power Rating DC	2.1 W
Insulation Initial Dielectric Between Contacts & Coil	500 Vrms

**Body Features** 



Product Weight	35 g[1.2 oz]
Enclosure Type	Dust Protected
Contact Features	
Contact Material	Silver Alloy
Termination Features	
Main Termination & Connection Type	Quick Connect Terminals
Coil Termination & Connection Type	Quick Connect Terminals
Mechanical Attachment	
Product Mount Type	Socket
Dimensions	
Product Width	25.9 mm[1.02 in]
Product Length	25.9 mm[1.02 in]
Product Height	24.9 mm[.98 in]
Usage Conditions	
Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Coil Magnetic System	Monostable
Current Type	DC
Other	
Environmental Ambient Temperature Class	105 – 125 °C
Contact Current Class	30 – 50 A
Height Class (Mechanical)	20 – 25 mm
Length Class (Mechanical)	25 – 30 mm
Width Class (Mechanical)	25 – 30 mm

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### **Compatible Parts**



## Also in the Series | Power Relay F



# **Customers Also Bought**














TE Part #2029030-3
3P MICRO MNL HDR ASY SR SIDE L







TE Part #10131358-00 QLS3854 H388/260 RB D4 JCB EAR C C1

TE Part #87780-000 PSS-X1005B PROXIMITY SENSOR

### **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-1414168-0\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1414168-0\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1414168-0\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

**Automotive Relay Application Notes** 

English

POWER F Change Over 40A Zust. B

English

General Purpose Power Relay, DC, Monostable, 1 Form C SPDT-CO, 20 A Contact Rating, 24 VDC Coil Voltage, 24 VDC Contact Voltage, Power Relay F



Power Relay F4, Mini ISO, Plug-In

English

**Product Specifications** 

Definitions General Purpose Relays

English