


Features

150 Watts peak pulse power ($t_p = 8/20\mu s$)
 Transient protection for high speed data lines to
 IEC 61000-4-2 (ESD) $\pm 30kV$ (air), $\pm 30kV$ (contact)
 IEC 61000-4-4 (EFT) 40A (5/50ns)
 Working voltages : 3.3V, 5V, 7V, 12V, 15V, 24V, 36V.
 Protects One Power or I/O Port
 Low operating and clamping voltages
 Solid-state silicon avalanche technology

SOD-523


Applications

Notebooks, Desktops, Servers and Video Graphics Cards
 USB Power & Data Line Protection
 Monitors and Flat Panel Displays
 I²C Bus Protection
 Portable Instrumentation
 Set Top Box





Maximum Rating @ $T_a = 25^\circ C$ unless otherwise specified

Symbol	Parameter	Ratings	Units
P_{PK}	Peak Pulse Power ($t_p = 8/20\mu s$)	150	Watts
T_L	Lead Soldering Temperature	260(10sec.)	$^\circ C$
T_J	Operating Temperature	-55 to +125	$^\circ C$
T_{STG}	Storage Temperature	-55 to +150	$^\circ C$

Electrical Characteristics@ Ta=25°C unless otherwise


Parameter	VRWM @ IR		VBR@ImA	VC@1	VC@IPP		CJ
	V	μA	V	V	V	A	pF
		MAX	MIN	MAX	MAX		MAX
SXESD5Z2.5	2.5	1	3.5	7.8	11	12	120
SXESD5Z3.3	3.3	1	4	9.8	13	12	120
SXESD5Z5.0	5	1	5.8	11.8	15	10	100
SXESD5Z6.0	6	1	6.5	12.8	17	9	80
SXESD5Z7.0	7	1	7.5	14	19	8	80
SXESD5Z12	12	1	13.3	19	25	6	70
SXESD5Z15	15	1	16.5	24	33	5	50
SXESD5Z18	18	1	19.8	32	45	4	40
SXESD5Z24	24	1	26.1	44	54	3	30
SXESD5Z36	36	1	38.2	62	80	3	30

Typical Characteristics@ $T_a=25^\circ\text{C}$ unless otherwise specified



Soldering Parameters




Reflow Condition		Fb – Free assembly
Pre Heat	- Temperature Min ($T_{s(Min)}$)	150°C
	- Temperature Max ($T_{s(Max)}$)	200°C
	- Time (Min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus) Temp (T_L) to peak		3°C/second Max
$T_{s(Max)}$ to T_L - Ramp-up Rate		3°C/second Max
Reflow	- Temperature (T_L) (Liquidus)	217°C
	- Temperature (t_L)	60 – 150 seconds
Peak Temperature (T_p)		250 ^{+0/-5} °C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second Max
Time 25°C to peak Temperature (T_p)		8 minutes Max.
Do not exceed		260°C



Package Outline

Plastic surface mounted package


SOD523



DIMENSIONS (mm are the original dimensions)

UNIT	A	b _P	c	D	E	H _E	v
mm	0.65 0.58	0.34 0.26	0.17 0.11	1.25 1.15	0.85 0.75	1.65 1.55	0.1

Soldering Footprint



Package And Marking Information

Device	Package	Shipping	Reel Size
TAPING	SOD523	3000/Reel	7 inch