




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Feed-Through**

Modular Terminal Block Product Type: **PI-Spring Terminal Block**

Primary Product Color: **Blue & Gray**

Product Spacing: **14 mm [.551 in]**

Number of Positions: **3**

Features

Product Type Features

Modular Terminal Block Product Type	PI-Spring Terminal Block
-------------------------------------	--------------------------

Configuration Features

Gauge Type	A7 & 6.3 mm Dia.
Number of Levels	1
Block Function	Feed-Through
Number of Positions	3

Electrical Characteristics

Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	1000 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (CSA)	75 A
Power Loss	2.4 W
Dielectric Withstanding Voltage (Max)	2200 V
Short-Time Withstanding Current Rating @ 1s	1920 A
Current Rating (UL)	75 A



Current Rating (IEC)	76 A
Body Features	
Product Weight	48.01 g[1.89 oz]
Primary Product Color	Blue & Gray
Mechanical Attachment	
DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail
Housing Features	
Housing Material	Polyamide
Dimensions	
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	.5 – 25 mm²
Main Circuit Capacity - Twin Ferrule per Spring Clamp	.5 – 6 mm²
Wire Stripping Length	15 mm[.591 in]
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	.5 – 16 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	20 – 6 AWG
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 16 mm²
Tool Size	4 mm[.157 in]
Product Depth	98.3 mm
Product Length	98.3 mm[3.87 in]
Product Height	47.5 mm
Product Spacing	14 mm[.551 in]
Usage Conditions	
Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
Industry Standards	
IP Rating	IP20
UL Flammability Rating	UL 94V-0
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant




EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1SNK160000R0000
MC812



TE Part # 1SNK900002R0000
BAZ1



TE Part # 1SNK900107R0000
CS-R3



TE Part # 1SNK900203R0000
TP2



TE Part # 1SNK900205R0000
TP4




TE Part # 1SNK169999R0000
MC812PA



TE Part # 1SNK900611R0000
UMH

Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(320)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)


Customers Also Bought



TE Part #1SNK150000R0000
MC612



TE Part #1SNK712011R0000
ZK16-3P



TE Part #1SNK912302R0000
JB12-2



TE Part #1SNK705072R0000
ZK2.5-3P-WH



TE Part #1SNK706021R0000
ZK4-3P-BL



TE Part #1SNK706022R0000
ZK4-4P-BL




TE Part #1SNK706031R0000
ZK4-3P-OR



TE Part #1SNK706060R0000
ZK4-YL



TE Part #1SNK706062R0000
ZK4-RD



TE Part #1SNK905350R0000
JB5-50

Documents

CAD Files

Customer View Model

ENG_CVM_CVM_1SNK712067R0000_A2.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK712067R0000_A2.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1SNK712067R0000_A2.2d_dxf.zip

1SNK712067R0000

Feed-Through, PI-Spring Terminal Block, Blue & Gray, Product Spacing 14 mm [.551 in], 3 Position, DIN Rail, ENTRELEC SNK, Modular Terminal Blocks



English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

ZK16-3P-PV-BL

English

SNK SERIES TERMINAL BLOCKS

English

Agency Approvals

UL

English