



RECOMMENDED LAND PATTERN DIMENSION OF P.C.B. (MOUNTING SIDE)



NOTE 1 HRS MARK SHOULD BE OPTIONAL.

1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
2. FOR MODIFICATION, ETC., PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
3. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

1	PPS	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min.				
					LEAD AREA:TIN-PLATING 1μm min.				
					UNDER PLATING:NICKEL 1μm min.				
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS			
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA		07. 01. 12	DRAWING NO.		EDC3-071644-21		
		CHECKED : HS. OZAWA		07. 01. 12	PART NO.		FX6A-50P-0. 8SV2 (71)		
		DESIGNED : KT. DOI		07. 01. 12	CODE NO.		CL576-0244-5-71		
		DRAWN : TS. MIYAKI		07. 01. 11			 		