

Specification Sheet

Part Number: T30R9C2



Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Natural, 100/pkg

Article Number	112-03019
Type	T30R
Color	Natural (NA)
Features & Benefits	• Inside serrations allow for strong grip on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Natural, 100/pkg

Global Part Name	T30R-PA66-NA
Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135.0
Length L (Imperial)	5.8
Length L (Metric)	147.32
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14
Width W (Metric)	3.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2

Material	Polyamide 6.6 (PA66)		
Material Shortcut	PA66		
US MIL SPEC	MS3367-5-9, Class 2		
SAE-AS33671			
Flammability			
UL 94 V2			Halogen free
Yes			Operating Temperature (Metric)
-40°F to +185°F (-40°C to +85°C)			Reach Complaint(Article 33)
Yes			ROHS Complaint
Yes			Certification/Specification WEB
CAGE Code 53421 Bundesamt für Wehrtechnik VG 95387 Part 4 Edition: 2008-12 DNV GL IEC 62275:2006			UL Recognized (US)
Yes			UL Listed (US and Canada)
Yes			UL Recognized (US and Canada)
Yes			UL Listed (US
Yes			
Package Quantity(Imperial)	100		

Package Quantity (Metric)

100

Customs Number

3926909988

Content Unit(BMEcat)

pcs.

Weight (Metric)

0.7