

GRM32MR72A393MA01#

" # " indicates a package specification code.

Available

General

125℃


Reflow OK

RoHS

Lead free

< List of part numbers with package codes >
GRM32MR72A393MA01L , GRM32MR72A393MA01K

Shape

	
L size	3.2 ± 0.3mm
W size	2.5 ± 0.2mm
T size	1.15 ± 0.1mm
External terminal width e	0.3mm min.
Distance between external terminals g	1.0mm min.
Size code in inch(mm)	1210 (3225)

Specifications

Capacitance	39000pF ± 20%
Rated voltage	100Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

References

Packaging	Specifications	Minimum quantity
L	φ 180mm Embossed taping	3000
K	φ 330mm Embossed taping	10000

Mass (typ.)	
1 piece	50mg
φ 180mm Reel	200g

⚠ Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.