



Connectors > Contacts > Connector Contacts



Contact Type: **Pin**

Contact Mating Area Plating Material: **Gold**

Wire Contact Termination Area Plating Material: **Gold**

Operating Voltage: **600 VDC**

Features

Product Type Features

Sealable	No
----------	----

Electrical Characteristics

Operating Voltage	600 VDC
-------------------	---------

Contact Features

Mating Pin Diameter	3.6 mm[.142 in]
Contact Underplating Material Thickness	1.27 µm[50 µin]
Wire Contact Termination Area Plating Thickness	.8 – 1.4 µm[30 µin]
Wire Contact Termination Area Plating Material Finish	Bright
Contact Mating Area Plating Material Thickness	.8 – 1.4 µm[30 µin]
Contact Mating Area Plating Material Finish	Bright
Contact Orientation	Straight
Contact Underplating Material	Nickel
Contact Type	Pin
Contact Mating Area Plating Material	Gold
Wire Contact Termination Area Plating Material	Gold



Contact Retention Within Housing	With
Contact Size	Size 8
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	21 A

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Wire Size	.8 – 1.4 mm ²
-----------	--------------------------

Usage Conditions

Operating Temperature Range	-55 – 130 °C[-67 – 266 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (3.7% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 318813-1
EXTRACTION TOOL ASSY



TE Part # 608668-1
HAND TOOL FRAME DANIELS



TE Part # 608668-2
POSITIONER DANIELS TP 731

Also in the Series | METRIMATE Power VIII



Connector Contacts(10)



Insertion & Extraction Tools(2)

Customers Also Bought



TE Part #5165424002
NTFR-5/8-0-SP



TE Part #487544-2
005 HOUSING FFC RCPT 050CL SR



TE Part #1-770247-0
UMNL II SOK SN/AUNI/PHBZ LP



TE Part #212008-1
CONTACT, SKT, PWR 8





TE Part #1-111492-5
010 UNIV I/O 30DP NO EARS LTCH



TE Part #4-641217-0
10P MTA156 CONN ASSY 18AWG
ORA

TE Part #819097N004
381A302-51-0-CS8581

TE Part #526595M014
NTFR-1-0-SP-CS5445

Documents

Product Drawings

SIZE 8 PIN CONT ASSY,16-18 AWG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_213567-1_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_213567-1_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_213567-1_G.3d_stp.zip

English

Customer View Model

ENG_CVM_213567-1_D.3d_igs.zip

English

Customer View Model

ENG_CVM_213567-1_D.3d_stp.zip

English

Customer View Model

ENG_CVM_213567-1_D.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Power Contacts

English

Product Specifications

Product Specification

Japanese

213567-1

Pin Contact, Gold, 600 VAC, 600 VDC, Size 8 Contact Size, 18 – 16 AWG Wire Size, .8 – 1.4 mm² Wire Size, Crimp, Copper Alloy, METRIMATE Power VIII

