



Representative Image

### Catalog No. 5252

**Description:** 1/2 NON-INSUL 90 DEG LT CONN

**UPC No** 786210052526

**Home > Cable Protection Systems > T&B Liquidtight Fittings > Liquid tight connectors**

Liquidtight Conduit Fitting, 90 Degree 1/2 Inch, Non-Insulated Malleable Iron

#### Descriptors

Category	Liquid tight connectors
Type	Connectors-90 Degree
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

#### Specifications

Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating

#### Classifications

Brand Name	T&B Liquidtight Fittings
Standard	UL E23018, CSA

#### Dimensions

Size	1/2 Inch
------	----------

#### Compliance and Certifications

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1/2 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT
Thread connection size	Other

ETIM	EC001180 Screw connection for protective metallic hose
One-piece	N
Material housing	Other
Surface protection	Other
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y