

### Description

The SX130N20MP is silicon N-channel Enhanced VDMOSFETs, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency.

### General Features



$V_{DS} = 200V$   $I_D = 130A$

$R_{DS(ON)} < 23m\Omega$  @  $V_{GS}=10V$

### Application

Uninterruptible Power Supply(UPS)

Power Factor Correction (PFC)



### Absolute Maximum Ratings ( $T_c=25^{\circ}C$ unless otherwise noted)

| Symbol   | Parameter                                        | Value           | Unit          |
|----------|--------------------------------------------------|-----------------|---------------|
|          |                                                  | TO-247-3L       |               |
| VDSS     | Drain-Source Voltage ( $V_{GS} = 0V$ )           | 200             | V             |
| ID       | Continuous Drain Current                         | 130             | A             |
| IDM      | Pulsed Drain Current (note1)                     | 360             | A             |
| VGS      | Gate-Source Voltage                              | $\pm 20$        | V             |
| EAS      | Single Pulse Avalanche Energy (note2)            | 2000            | mJ            |
| IAR      | Avalanche Current (note1)                        | 30              | A             |
| EAR      | Repetitive Avalanche Energy (note1)              | 25              | mJ            |
| Pd       | Power Dissipation ( $T_c = 25^{\circ}C$ )        | 450             | W             |
| TJ, Tstg | Operating Junction and Storage Temperature Range | $-55 \sim +150$ | $^{\circ}C$   |
| RthJC    | Thermal Resistance, Junction-to-Case             | 1.2             | $^{\circ}C/W$ |
| RthJA    | Thermal Resistance, Junction-to-Ambient          | 40              | $^{\circ}C/W$ |







**Electrical Characteristics (T<sub>J</sub>=25°C, unless otherwise noted)**

| Symbol          | Parameter                          | Test Conditions                                                            | Min. | Typ. | Max. | Unit |
|-----------------|------------------------------------|----------------------------------------------------------------------------|------|------|------|------|
| V(BR)DSS        | Drain-Source Breakdown Voltage     | V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA                               | 200  | 220  | --   | V    |
| IDSS            | Zero Gate Voltage Drain Current    | V <sub>DS</sub> = 200V, V <sub>GS</sub> = 0V, T <sub>J</sub> = 25°C        | --   | --   | 5    | μA   |
|                 |                                    | V <sub>DS</sub> = 160V, V <sub>GS</sub> = 0V, T <sub>J</sub> = 125°C       | --   | --   | 100  |      |
| IGSS            | Gate-Source Leakage                | V <sub>GS</sub> = ±20V                                                     | --   | --   | ±100 | nA   |
| VGS(th)         | Gate-Source Threshold Voltage      | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA                 | 2.0  | 3.0  | 4.0  | V    |
| RDS(on)         | Drain-Source On-Resistance (Note3) | V <sub>GS</sub> = 10V, I <sub>D</sub> = 9A                                 | --   | 18   | 23   | mΩ   |
| Ciss            | Input Capacitance                  | V <sub>GS</sub> = 0V,<br>V <sub>DS</sub> =25V, f=1.0MHz                    | --   | 6500 | --   | pF   |
| Coss            | Output Capacitance                 |                                                                            | --   | 980  | --   |      |
| Crss            | Reverse Transfer Capacitance       |                                                                            | --   | 370  | --   |      |
| Qg              | Total Gate Charge                  | V <sub>DD</sub> = 160V, I <sub>D</sub> = 90A, V <sub>GS</sub> = 10V        | --   | 200  | --   | nC   |
| Qgs             | Gate-Source Charge                 |                                                                            | --   | 28   | --   |      |
| Qgd             | Gate-Drain Charge                  |                                                                            | --   | 60   | --   |      |
| td(on)          | Turn-on Delay Time                 | V <sub>DD</sub> =100V, I <sub>D</sub> =90A, R <sub>G</sub> =25 Ω           | --   | 45   | --   | ns   |
| t <sub>r</sub>  | Turn-on Rise Time                  |                                                                            | --   | 70   | --   |      |
| td(off)         | Turn-off Delay Time                |                                                                            | --   | 110  | --   |      |
| t <sub>f</sub>  | Turn-off Fall Time                 |                                                                            | --   | 90   | --   |      |
| I <sub>S</sub>  | Continuous Body Diode Current      | T <sub>C</sub> = 25 °C                                                     | --   | --   | 90   | A    |
| ISM             | Pulsed Diode Forward Current       |                                                                            | --   | --   | 360  |      |
| VSD             | Body Diode Voltage                 | T <sub>J</sub> = 25°C, I <sub>SD</sub> = 90A, V <sub>GS</sub> = 0V         | --   | --   | 1.4  | V    |
| t <sub>rr</sub> | Reverse Recovery Time              | V <sub>GS</sub> = 0V, I <sub>S</sub> = 90A, di <sub>F</sub> /dt = 100A /μs | --   | 280  | --   | ns   |
| Q <sub>rr</sub> | Reverse Recovery Charge            |                                                                            | --   | 2.4  | --   | μC   |

**Note :**

- 1、The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper.
- 2、The EAS data shows Max. rating . I<sub>AS</sub> = 30A, V<sub>DD</sub> = 50V, R<sub>G</sub> = 25 Ω, Starting T<sub>J</sub> = 25 °C
- 3、The test condition is Pulse Test: Pulse width ≤ 300μs, Duty Cycle ≤ 1%
- 4、The power dissipation is limited by 150°C junction temperature
- 5、The data is theoretically the same as ID and IDM , in real applications , should be limited by total power dissipation.

## Typical Characteristics



## Typical Characteristics




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10. Maximum Avalanche Energy Vs. Drain Current





Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case

**Package Mechanical Data-TO-247-3L**


| Dim. | Min.     | Max. |
|------|----------|------|
| A    | 15.0     | 16.0 |
| B    | 20.0     | 21.0 |
| C    | 41.0     | 42.0 |
| D    | 5.0      | 6.0  |
| E    | 4.0      | 5.0  |
| F    | 2.5      | 3.5  |
| G    | 1.75     | 2.5  |
| H    | 3.0      | 3.5  |
| I    | 8.0      | 10.0 |
| J    | 4.9      | 5.1  |
| K    | 1.9      | 2.1  |
| L    | 3.5      | 4.0  |
| M    | 4.75     | 5.25 |
| N    | 2.0      | 3.0  |
| O    | 0.55     | 0.75 |
| P    | Typ 5.08 |      |
| Q    | 1.2      | 1.3  |

**Package Marking and Ordering Information**

| Product ID | Pack      | Marking | Qty(PCS) |
|------------|-----------|---------|----------|
| TAPING     | TO-247-3L |         | 330      |