

Part Number: 780480643

**Product Description :** 1.50mm Pitch Pico-SPOX Wire-to-Board Header, Liquid Crystal Polymer, Right-Angle, 6 Circuits, Embossed Tape on

Reel, Beige Status: Active

Series Number: 78048

**Product Category: PCB Headers and** 

Receptacles

#### **Documents & Resources**

#### **Drawings**

Drawing 780480643\_sd.pdf

### 3D Models and Design Files

2D Drawing DXF 780480643.dxf

2D Drawing DXF (PDF) 780480643.pdf

3D Model 780480643\_stp.zip

#### **Specifications**

Packaging Specification SPK-78048-001-001.pdf Product Specification PS-78047-001-001.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Compliant with Exemption 44; 33
China RoHS	•
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

## **Part Details**

## General

Status	Active
Category	PCB Headers and Receptacles
Series	78048
Description	1.50mm Pitch Pico-SPOX Wire-to- Board Header, Liquid Crystal Polymer, Right-Angle, 6 Circuits, Embossed Tape on Reel, Beige
Application	Signal, Wire-to-Board
Component Type	PCB Header
Product Family	Pico-SPOX Wire-to-Board Connector System
Product Name	Pico-SPOX
UPC	800756707198

## Agency

CSA	LR19980
UL	E29179

### **Electrical**

Current - Maximum per Contact	2.5A
Voltage - Maximum	250V AC

## Physical

Breakaway	No
Circuits (Loaded)	6
Circuits (maximum)	6
Color - Resin	Beige
Durability (mating cycles max)	10
First Mate / Last Break	No

Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Material - Resin	Liquid Crystal Polymer
Net Weight	0.402/g
Number of Rows	1
Orientation	Right Angle
Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Retention	None
Pitch - Mating Interface	1.50mm
Plating min - Mating	2.540µm
Plating min - Termination	2.540µm
Polarized to Mating Part	Yes
Polarized to PCB	No
Shrouded	Fully
Stackable	No
Temperature Range - Operating	-55° to +105°C
Termination Interface Style	Surface Mount

# Mates With / Use With

## Mates with Part(s)

Description	Part Number
Pico-SPOX Single Row Receptacle Housings	<u>87439</u>

## Use with Part(s)

Description	Part Number
Pico-SPOX Female Crimp Terminals	<u>87421</u>

This document was generated on Sep 18, 2024