

PERFORMANCE CHARACTERISTICS :

CURRENT RATING : 1.5A AT 20°C (FULLY LOADED)
1A AT 70°C (FULLY LOADED)
RATED VOLTAGE : 500V AC (CONT / CONT)
OPERATING TEMPERATURE : -55°C TO 125°C
CONTACT RESISTANCE : 25mΩ MAX.
INSERTION FORCE : 0.75 N MAX / CONT
EXTRACTION FORCE : 0.15 N MIN / CONT
INSULATION RESISTANCE : 10⁴ MΩ MIN.

NOTES :

1. UL APPROVED WITH USR AND CNR.
2. MEASURED AT THE BOTTOM.
3. MATERIAL CONTACT : PHOSPHORBRONZE.
HOUSING : LCP 30% GLASS-FILLED
4. CONNECTOR PRINTED WITH P/N AND DATE CODES.
5. FOR ACTUAL CONTACT LOADINGS, SEE LOADING
PATTERN MATING SIDE.}
6. 4 = LEVEL 1 (5.30)
5 = LEVEL 2 (6.80)
6 = LEVEL 3 (8.30)
7. 'HM2J07PE5IA8' LEAD FREE INDICATOR : LF = LEAD FREE
PERFORMANCE LEVEL INDICATOR
(Ref DWG No BS,C ,201844,003)
8. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS,A ,201572,001
9. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-47-0004

LOADING PATTERN : MATING SIDE

F	6	6	6	6	6	6	6	6	6	6	6	X	X	X	6	6	6	6	6	6	6	6	6	6	6
E	5	5	4	5	5	5	4	6	5	6	5	X	X	X	5	6	5	6	5	4	5	5	5	5	5
D	5	5	4	5	5	5	4	6	5	6	5	X	X	X	5	6	5	6	5	4	5	5	5	5	5
C	5	5	4	5	5	5	4	6	6	6	6	X	X	X	6	6	6	6	5	4	5	5	5	5	5
B	5	5	4	5	5	5	4	5	5	5	5	X	X	X	5	5	5	5	5	4	5	5	5	5	5
A	5	5	4	5	5	5	4	6	5	6	5	X	X	X	5	6	5	6	5	4	5	5	5	5	5
Z	0	0	0	0	0	0	0	0	0	0	0	X	X	X	0	0	0	0	0	0	0	0	0	0	0
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25

spec ref -				dr P-Mathew Nebu		2011/05/25		projection				size mm		A3		scale 1/1	
tolerance std				eng Alex Babu		2020/07/27						ecn no ELX-I-37774-1					
ISO 406				chr -		-											
ISO 1101				appr Kuriakose, San		2020/07/27						product family MILLIPACS					
surface		linear		0.X		±0.2		Amphenol FCI				title MPACS RA HDR		dwg no BSC202767039		rev G	
				0.XX		±0.1											
				0.XXX		±0.05											
		ISO 1302		angular		0°		±1°		cat. no. HM2J07PE51A8----		Product - Customer Drw				sheet 1 of 1	