MAG-MATE

TE Internal #: 964290-1

Poke-In, Lead Wire Size 20-18 AWG, Lead Wire Size .5-1 mm², Crimp / Insulation Displacement (IDC), MAG-MATE, Magnet Wire

Terminals

View on TE.com >



Terminals & Splices > Magnet Wire Terminals











Magnet Wire Terminal Type: Poke-In

Compatible With Discrete Wire Type

Compatible Insulation Diameter (Max): 2.31 mm [.091 in]

Compatible Insulation Diameter Range: 1.6 – 2.31 mm [.063 – .091 in]

Lead Wire Size: .5 – 1 mm²

Features

Product Type Features

Contact Features	
Magnet Wire Terminal Type	Poke-In
Terminal Plating Material	Tin
Terminal Orientation	Straight
Termination Features	

Lead Wire

Termination Method to Wire & Cable	Crimp, Insulation Displacement (IDC)
Crimp Area Length	6.2 mm[.244 in]

Mechanical Attachment

Wire Insulation Support With

Dimensions

Terminal Height	20.5 mm[.807 in]
Compatible Insulation Diameter (Max)	2.31 mm[.091 in]
Compatible Insulation Diameter Range	1.6 – 2.31 mm[.063 – .091 in]



Lead Wire Size	$.5 - 1 \text{ mm}^2$
Product Length	7.9 mm[.311 in]
Usage Conditions	
Insulation Option	Uninsulated
Operation/Application	
Compatible With Wire Base Material	Copper
Packaging Features	
Packaging Quantity	6000

Reel, Reel/Carton

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | MAG-MATE







Insertion & Extraction Tools(6)



Magnet Wire Terminals(337)



Customers Also Bought



TE Part #350669-1 UMNL GRND PIN 20-14 PTPBR L/P



TE Part #175193-1 187 PL EX FLAG REC. 22-16AWG PTBR



TE Part #62833-1 MAG-MATE POKE-IN TERM 016TPBR





TE Part #293041-1 FF 250 TAB 0.35-1.0MM2 BR



TE Part #2825575-2 MAG-MATE Slim Line with Multispring



TE Part #2-1481643-3 **GUIDE PLATE FRONT**



Documents

Product Drawings

POKE-IN FLA-STECKER

English

CAD Files

Customer View Model

ENG_CVM_964290-1_C.3d_igs.zip

English

Customer View Model



ENG_CVM_964290-1_C.3d_stp.zip

English

Customer View Model

ENG_CVM_964290-1_C.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Magnet Wire Terminals & Splices

English