

Search within category

GO

BUY NOW

DESIGN / INSTALL



PN10-10RN-D

Ring Terminal, 12 – 10 AWG, #10 narrow stud size, nylon insulated, bulk package.

Specs

Packaging Details

Tools

Documents

★ Add to Favorites

 Add to BOM

Stud Size	#10
Stud Size Metric	M5
Wire Range	12 AWG - 10 AWG
Wire Range (mm²)	4.0 - 6.0
Barrel Configuration	Standard
Barrel Type	Insulation Grip Sleeve
Base Material	Copper
Insulation	Nylon
Panduit Color Code	Yellow
Plating Type	Tinned
Part Number Series	PN
Clearance	0.31
Clearance (mm)	7.9
Length (In.)	1.04
Length (mm)	26.4
Max. Insulation Diameter In. (mm)	0.225 (5.7)
Stock	0.04
Stock (mm)	1.0
Flammability Rating	UL 94V-2/HB
Max. Voltage Rating	600 V
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
CA-800/EZ Series Crimp Die	—
CA9 Series Crimp Die	—
Tool	CT-100A, CT-600-A, CT-1550, CT-1551, CT-2500
CSACertified	C22.2 No. 65
MI. Std. Part Number	—
UL Listed	Yes
Packaging Type	Box
RoHS Compliancy Status	Compliant
Min. Order Qty.	500

We Welcome Your Feedback! Help Us Improve By Taking Our Short Survey

Give Feedback