




PLASTI-GRIP

TE Internal #: 2-34159-1  
Closed Ring Tongue Terminal, 16 – 14 AWG, #6 / M3.5 Stud Size,  
3.68 mm [.145 in] Stud Diameter, Closed Barrel, Straight, Tin,  
PLASTI-GRIP

[View on TE.com >](#)

Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 2050 – 5180 CMA

Stud Size: #6, M3.5

Features

Product Type Features

|                                        |                             |
|----------------------------------------|-----------------------------|
| Ring Terminal Product Type             | Closed Ring Tongue Terminal |
| Stud Size                              | #6, M3.5                    |
| Sealable                               | No                          |
| Wire Insulation Support Retention Type | Insulation Support          |

Configuration Features

|                 |   |
|-----------------|---|
| Number of Holes | 1 |
|-----------------|---|

Electrical Characteristics

|                |       |
|----------------|-------|
| Voltage Rating | 600 V |
|----------------|-------|

Body Features

|                |        |
|----------------|--------|
| Product Weight | .874 g |
|----------------|--------|

Contact Features

|                           |          |
|---------------------------|----------|
| Barrel Type               | Closed   |
| Terminal Orientation      | Straight |
| Terminal Plating Material | Tin      |

Mechanical Attachment



|                         |      |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|

Dimensions

|                                      |                            |
|--------------------------------------|----------------------------|
| Wire Size                            | 2050 – 5180 CMA            |
| Stud Diameter                        | 3.68 mm[.145 in]           |
| Tongue Thickness                     | .79 mm[.031 in]            |
| Product Length                       | 22.12 mm[.87 in]           |
| Compatible Insulation Diameter (Max) | 4.9 mm[.193 in]            |
| Compatible Insulation Diameter Range | 3 – 4.9 mm[.118 – .193 in] |

Usage Conditions

|                             |                     |
|-----------------------------|---------------------|
| Insulation Option           | Partially Insulated |
| Operating Temperature Range | 105 °C[221 °F]      |

Operation/Application

|                                       |        |
|---------------------------------------|--------|
| Compatible With Wire Base Material    | Copper |
| Compatible With Wire Plating Material | Tin    |

Industry Standards

|                               |    |
|-------------------------------|----|
| Government Qualified Terminal | No |
|-------------------------------|----|

Packaging Features

|                    |              |
|--------------------|--------------|
| Packaging Quantity | 5000         |
| Packaging Method   | Tape Mounted |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                                  |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                    |



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 58423-1  
DIE, RBY IS9252

TE Part # 59824-1  
TETRA-CRIMP PIDG PG FASTON 22-10 ASSY

TE Part # 58433-3  
PRO CR ASSY, RBY IS9252

TE Part # 47387  
DAHT PG PIDG 20-14 ASSY

TE Part # 169404  
CERTI-LOK DIE

TE Part # 1SET191002R0000  
TET CRIMP-HT

Also in the Series | PLASTI-GRIP

Compression Connectors(3)

Crimp Wire Pins, Tabs & Ferrules(19)

Ring Terminals(300)

Spade Terminals(159)





Splices(45)

Customers Also Bought



TE Part #1-640456-5  
15P MTA100 HDR ASSY F/L SQ STR



TE Part #1-322985-0  
TERMINAL,PIDG SPD 12-10 6




TE Part #52955-2  
TERMINAL,PG SPR SPD 16-14 6



TE Part #640907-2  
RECEPT,PIDG FASTON 12-10 250



TE Part #61119-2  
PIN RECPT .058 R/A PTPPHBZ



TE Part #552731-1  
KIT, 90 COVER, 50 POS



TE Part #58075-1  
MTA 50/100/156 PNEUMATIC TOOL FRAME



TE Part #2151496-1  
OCEAN\_2.0\_APPLICATOR-S-055F062O-RSM



TE Part #7-2151496-7  
OCEAN\_2.0\_SPARE\_PART\_KIT-055F062O



TE Part #2217347-1  
LED WORKLIGHT ASSY

Documents

Product Drawings

TERMINAL,PG R 16-14 6

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2-34159-1\_W.2d\_dxf.zip



English

Customer View Model

[ENG\\_CVM\\_CVM\\_2-34159-1\\_W.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_2-34159-1\\_W.3d\\_stp.zip](#)

English

[3D PDF](#)

English

Customer View Model

[ENG\\_CVM\\_2-34159-1\\_K1.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_2-34159-1\\_K1.3d\\_stp.zip](#)

English

Customer View Model

[ENG\\_CVM\\_2-34159-1\\_K1.2d\\_dxf.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

**Product Specifications**

[Application Specification](#)

English

**Agency Approvals**

[UL Report](#)

English