UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Conductor marker, Sheet, red, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 1.5 ... 14 mm, lettering field size: 30 x 4 mm, Number of individual labels: 30

Your advantages

- The UCT-WMT ... UniCard marking range includes markers for wire marking with marking sleeves from the PATG (HF) ... /PATO ... systems
- The markers, which are supplied in uniform sheets, can be marked quickly, easily, and precisely using the card printers
- The sheets provide additional space for project information and function text that can be helpful during further assembly
- The multi-section marking strips are easy to fit and can be easily separated if required
- Marking service: Phoenix Contact can custom-mark all UniCard markers according to your specifications

Commercial data

Item number	0801424
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG10
Product key	BG2218
Catalog page	Page 207 (C-3-2019)
GTIN	4046356677004
Weight per piece (including packing)	11.04 g
Weight per piece (excluding packing)	11 g
Customs tariff number	39269097
Country of origin	PL

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

Technical data

Product properties

Product type	Conductor marking

Marking

Number of individual labels	30
Number of individual labels per row	10
Identification technology	Thermal transfer for sheets and cards

Dimensions

Width	30 mm
Text field width	30.00 mm
Text field height	4.00 mm
Length	4 mm

Material specifications

RoHS compliant	yes
Color	red
Material	PC
Flammability rating according to UL 94	V0
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	free from silicone and halogen

Cable/line

External cable diameter	1.5 mm ... 14 mm

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed

n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)

Mounting

Mounting type	insert

Classifications

ECLASS

ECLASS-11.0	27281106
ECLASS-12.0	27281106
ECLASS-13.0	27281106

ETIM

ETIM 9.0	EC001530

UNSPSC

UNSPSC 21.0	39131700

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

UCT-WMT (30X4) RD - Conductor marker

Accessories

THERMOMARK CARD 2.0 - Thermal transfer printer

1085267

https://www.phoenixcontact.com/us/products/1085267

Thermal transfer printer for card materials, including Euro/US power cable and USB cable. User manual printed in German and English. Magazine for UCT-TM... . sheets and magazines for US-... cards. One packing unit each UCT-TM 6, US-EMLP (85,6x54), ink ribbon = 50 m

THERMOMARK PRIME 2.0 US - Thermal transfer printer

1472410

https://www.phoenixcontact.com/us/products/1472410

Thermal transfer printer for printing card materials with a print resolution of 300 dpi. Suitable for stationary as well as mobile use thanks a 7″ color touch display with integrated "MARKING system app" and a replaceable battery pack.

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

BLUEMARK ID - Printer

1003334

https://www.phoenixcontact.com/us/products/1003334

Monochrome printer with UV LED technology and integrated "MARKING system app" identification software. 7″ touch color display for printing plastic tags in UC, UCT, US, and UM format, as well as metal labels.

BLUEMARK ID COLOR - Printer

1002329

https://www.phoenixcontact.com/us/products/1002329

CMYK multicolor printer with UV LED technology, with integrated "MARKING system app" identification software, 7″ touch color display for printing plastic tags in UC, UCT, and UM format, as well as metal labels.

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

TOPMARK NEO - Laser marker

1012015

https://www.phoenixcontact.com/us/products/1012015

Laser marking system for the efficient marking of metal or plastic marking material from the LS…, UCT…, UC…/PP…, UM… product families.

THERMOMARK-RIBBON 110/50-TC - Ink ribbon

0801384

https://www.phoenixcontact.com/us/products/0801384

Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 50 m, roll length: 50 m, width: 110 mm, color: black

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

THERMOMARK-RIBBON 110-TC - Ink ribbon

0801371

https://www.phoenixcontact.com/us/products/0801371

Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 300 m, roll length: 300 m, width: 110 mm, color: black

TMP-RIBBON 110 BK 100 - Ink ribbon cartridge

0803374

https://www.phoenixcontact.com/us/products/0803374

Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups UCT. .., US..., and UM..., length: 70 m, roll length: 70 m, width: 110 mm, color: black

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

BM ID-CARTR. BK - Ink cartridge

1044345

https://www.phoenixcontact.com/us/products/1044345

Replacement UV fluid, 23 ml, color: black

BM ID-CARTR. CY - Ink cartridge

1044346

https://www.phoenixcontact.com/us/products/1044346

Replacement UV fluid, 23 ml, color: cyan

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

BM ID-CARTR. YE - Ink cartridge

1044348

https://www.phoenixcontact.com/us/products/1044348

Replacement UV fluid, 23 ml, color: yellow

BLUEMARK CLED-FLUID-CARTR. - Ink cartridge

5146662

https://www.phoenixcontact.com/us/products/5146662

Cartridge, for replacement, 20 ml UV color, black, including cleaning cartridge

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

BLUEMARK FLUID-CARTRIDGE - Ink cartridge

5147421

https://www.phoenixcontact.com/us/products/5147421

Cartridge, for replacement, 28 ml UV color, black including cleaning cartridge

TMP-UCT-MAG7 - Magazine

0803349

https://www.phoenixcontact.com/us/products/0803349

Magazine, for the THERMOMARK PRIME and the THERMOMARK CARD, for accommodating UCT-WMT..., UCT-EM (7x10), length: 0.166 m, width: 114 mm, height: 11.5 mm

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

BM ID-MAG20 - Magazine

1044356

https://www.phoenixcontact.com/us/products/1044356

Infeed magazine for accommodating a max. of 20 UniCard sheets

BM ID-MAG40 - Magazine

1044357

https://www.phoenixcontact.com/us/products/1044357

Infeed magazine for accommodating a maxi. of 40 UniCard sheets

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

TOPMARK LASER-MAG UCT-A - Magazine

0803141

https://www.phoenixcontact.com/us/products/0803141

Magazine for the TOPMARK LASER, for accommodating UCT material automatically

TOPMARK LASER-MAG UCT-M - Magazine

0803143

https://www.phoenixcontact.com/us/products/0803143

Magazine for the TOPMARK LASER, for accommodating UCT material manually

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

PAB-KTL - Cable marker carrier

1013261

https://www.phoenixcontact.com/us/products/1013261

Cable marker carrier, transparent, unlabeled, horizontal, mounting type: Assembly with cable ties, cable diameter: > 10 mm, lettering field size: 30 x 4 mm

PAB-SK 30 - Marker carriers

1013290

https://www.phoenixcontact.com/us/products/1013290

Marker carriers, transparent, unlabeled, mounting type: adhesive, lettering field size: 30 x 4 mm

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

PATG 1/30 - Conductor marker carrier

0822440

https://www.phoenixcontact.com/us/products/0822440

Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 1.5 ... 2.5 mm, lettering field size: 30 x 4 mm

PATG 2/30 - Conductor marker carrier

0822453

https://www.phoenixcontact.com/us/products/0822453

Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 30 x 4 mm

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

PATG 3/30 - Conductor marker carrier

0822466

https://www.phoenixcontact.com/us/products/0822466

Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 4 ... 7 mm, lettering field size: 30 x 4 mm

PATG 4/30 - Conductor marker carrier

0822479

https://www.phoenixcontact.com/us/products/0822479

Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 6 ... 10 mm, lettering field size: 30 x 4 mm

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

PATG 5/30 - Conductor marker carrier

0822482

https://www.phoenixcontact.com/us/products/0822482

Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 10 ... 14 mm, lettering field size: 30 x 4 mm

PATG HF 1/30 - Conductor marker carrier

1014049

https://www.phoenixcontact.com/us/products/1014049

Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 1.3 ... 2.8 mm, lettering field size: 30 x 4 mm

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

PATG HF 2/30 - Conductor marker carrier

1014055

https://www.phoenixcontact.com/us/products/1014055

Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 30 x 4 mm

PATG HF 3/30 - Conductor marker carrier

1014061

https://www.phoenixcontact.com/us/products/1014061

Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 4 ... 7 mm, lettering field size: 30 x 4 mm

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

PATG HF 3/30 VPE 1000 - Conductor marker carrier

1044263

https://www.phoenixcontact.com/us/products/1044263

Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 4 ... 7 mm, lettering field size: 30 x 4 mm

PATG HF 4/30 - Conductor marker carrier

1014067

https://www.phoenixcontact.com/us/products/1014067

Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 5 ... 10 mm, lettering field size: 30 x 4 mm

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

PATG HF 4/30 VPE 1000 - Conductor marker carrier

1044271

https://www.phoenixcontact.com/us/products/1044271

Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 5 ... 10 mm

PATO 1/30 - Conductor marker carrier

0822495

https://www.phoenixcontact.com/us/products/0822495

Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 2 ... 3.5 mm, lettering field size: 4 x 30 mm

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

PATO 2/30 - Conductor marker carrier

0822505

https://www.phoenixcontact.com/us/products/0822505

Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 2.8 ... 4.4 mm, lettering field size: 4 x 30 mm

THERMOMARK CARD - Thermal transfer printer

5146464

https://www.phoenixcontact.com/us/products/5146464

Thermal transfer printer for cards

UCT-WMT (30X4) RD - Conductor marker

0801424

https://www.phoenixcontact.com/us/products/0801424

BLUEMARK CLED - Printer

5147999

https://www.phoenixcontact.com/us/products/5147999

Printers with LED-UV technology for printing plastic labels in UniCard format.

THERMOMARK CARD-UCT-MAG7 - Magazine

0801734

https://www.phoenixcontact.com/us/products/0801734

Magazine for the THERMOMARK CARD printer, for accommodating UCT sheets (UCT-WMT...)

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com