

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260

<https://www.phoenixcontact.com/us/products/2907260>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in lightning current arrester, in accordance with Type 1/Class I, with integrated surge-proof fuse, for 3-phase power supply networks with combined PE and N installed in one conductor (L1, L2, L3, PEN).

Your advantages

- Surge protection family for universal use with optimum energy coordination from the lightning current arrester to the device protection
- Easy to maintain due to consistently pluggable protection modules
- Excellent level of information provided by mechanical/visual status indicator and remote indication contact
- Optimum protective effect in the event of high-energy lightning currents, thanks to spark gap technology with low residual voltage characteristic
- Integrated lightning-current-proof backup fuse for a low overall voltage protection level and space savings of up to 80% compared to an external backup fuse

Commercial data

Item number	2907260
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CL1163
Catalog page	Page 34 (C-4-2019)
GTIN	4055626176437
Weight per piece (including packing)	1,767 g
Weight per piece (excluding packing)	1,755 g
Country of origin	DE

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260

<https://www.phoenixcontact.com/us/products/2907260>

Technical data

Product properties

Product type	Combination type
Product family	SEC Family
IEC test classification	I / II
	T1 / T2
EN type	T1 / T2
IEC power supply system	TN-C
	TT
Type	DIN rail module, two-section, divisible
Number of positions	3
Surge protection fault message	Optical, remote indicator contact

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Electrical properties

Nominal frequency f_N	50 Hz (60 Hz)
-------------------------	---------------

Indicator/remote signaling

Connection name	Remote fault indicator contact
Switching function	Changeover contact
Operating voltage	12 V AC ... 250 V AC
	125 V DC (200 mA DC)
Operating current	10 mA AC ... 1 A AC
	1 A DC (30 V DC)

Connection data

Connection method	Screw connection
Screw thread	M5
Tightening torque	4.5 Nm
Stripping length	18 mm
Conductor cross section flexible	2.5 mm ² ... 35 mm ²
Conductor cross section rigid	2.5 mm ² ... 35 mm ²
Conductor cross section AWG	13 ... 2
Connection method	Fork-type cable lug
Conductor cross section flexible	1.5 mm ² ... 16 mm ²

Remote fault indicator contact

Connection method	Plug-in/screw connection via COMBICON
Screw thread	M2

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester




2907260

<https://www.phoenixcontact.com/us/products/2907260>

Tightening torque	0.25 Nm
Stripping length	7 mm
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section rigid	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16

Dimensions

Dimensional drawing	
Width	106.8 mm
Height	167 mm
Depth	74.5 mm
Horizontal pitch	6 Div.

Material specifications

Color (Male connector)	light grey (RAL 7035)
Color (Base element)	gray (RAL 7042)
Flammability rating according to UL 94	V-0
CTI value of material	600
Insulating material	PA 6.6-FR 20% GF PBT-FR
Material group	I
Housing material	PA 6.6-FR 20 % GF PBT-FR

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Protective circuit

Mode of protection	L-PEN L-PE
Direction of action	3L-N/PE
Nominal voltage U_N	400/690 V AC (TN-C) 400 V AC (IT)
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous voltage U_C	440 V AC
Residual current I_{PE}	$\leq 5 \mu A$
Nominal discharge current I_n (8/20) μs	25 kA
Maximum discharge current I_{max} (8/20) μs	50 kA

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260

<https://www.phoenixcontact.com/us/products/2907260>

Impulse discharge current (10/350) μ s, charge	12.5 As
Impulse discharge current (10/350) μ s, specific energy	160 kJ/ Ω
Impulse discharge current (10/350) μ s, peak value I_{imp}	25 kA
Follow current interrupt rating I_{fi}	50 kA
Short-circuit current rating I_{SCCR}	50 kA
Voltage protection level U_p	≤ 2.5 kV
Residual voltage U_{res}	≤ 2.1 kV (at I_n)
	≤ 2.8 kV (at 50 kA)
	≤ 1.7 kV (at 12.5 kA)
	≤ 1.5 kV (at 5 kA)
	≤ 1.35 kV (at 2.5 kA)
Front of wave sparkover voltage at 6 kV (1.2/50) μ s	≤ 2.5 kV
TOV behavior at U_T	580 V AC (5 s / withstand mode)
	760 V AC (120 min / withstand mode)
	1640 V AC (200 ms / safe failure mode)
Response time t_A	≤ 100 ns

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20 (only when all terminal points are used)
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl)
Permissible humidity (operation)	5 % ... 95 %

Standards and regulations

Standards/specifications	IEC 61643-11
Note	2011

EN 61643-11

Standards/specifications	EN 61643-11
Note	2012

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------


FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester

2907260


<https://www.phoenixcontact.com/us/products/2907260>

Drawings

Dimensional drawing



Circuit diagram




FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester

2907260


<https://www.phoenixcontact.com/us/products/2907260>

Application drawing



Structure of a 3+1 circuit for TN-S/TT systems with an N/PE spark gap and wiring bridge.

Application drawing



FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260

<https://www.phoenixcontact.com/us/products/2907260>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2907260>



IECEE CB Scheme

Approval ID: NL-41433



EAC

Approval ID: RU C-DE.*09.B.00169

CCA

Approval ID: NTR-NL 7490



KEMA-KEUR

Approval ID: 2188437.01

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260
<https://www.phoenixcontact.com/us/products/2907260>

Classifications

ECLASS

ECLASS-11.0	27130802
ECLASS-13.0	27171201

ETIM

ETIM 9.0	EC000381
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260
<https://www.phoenixcontact.com/us/products/2907260>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	N,N-dimethylacetamide(CAS: 127-19-5)
SCIP	f926deff-9d51-4c74-8d1d-599be016c1b4

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260

<https://www.phoenixcontact.com/us/products/2907260>

Accessories

i Note: Applying some accessories below might limit this product.

MPB 18/1-8/35 - Wiring bridge

2908704

<https://www.phoenixcontact.com/us/products/2908704>




Wiring bridge for modules with 17.5 mm connecting pitch, 1-phase, 8-pos., 35 mm² cross section, and mounted end caps

i Max. current carrying capacity: 125 A

MPB 18/1-6/35 - Wiring bridge

2908705

<https://www.phoenixcontact.com/us/products/2908705>



Wiring bridge for modules with 17.5 mm connecting pitch, 1-phase, 6-pos., 35 mm² cross section, and mounted end caps

i Max. current carrying capacity: 125 A

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260


<https://www.phoenixcontact.com/us/products/2907260>

FLT-SEC-H MPB-3+1 - Wiring bridge

2910501

<https://www.phoenixcontact.com/us/products/2910501>

Wiring bridge for connecting three FLASHTRAB SEC HYBRID lightning arresters with an N/PE spark gap to a 3+1 circuit for TN-S-/TT systems. Connecting pitch of 17.5 mm, 1-phase, 8-pos., 35 mm² cross section with stable plastic housing for the required touch proofness when used as neutral conductor bridge.



CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/us/products/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260

<https://www.phoenixcontact.com/us/products/2907260>

EML (20XE)R - Label

0803452

<https://www.phoenixcontact.com/us/products/0803452>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: continuous x 20 mm, Number of individual labels: 1

EML (20XE)R YE - Label

0803453

<https://www.phoenixcontact.com/us/products/0803453>



Label, Roll, yellow, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: continuous x 20 mm, Number of individual labels: 1

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260

<https://www.phoenixcontact.com/us/products/2907260>

X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/us/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

SZK PZ2 VDE - Screwdriver

1206463

<https://www.phoenixcontact.com/us/products/1206463>



Screwdriver, PZ crosshead, VDE insulated, size: PZ 2 x 100 mm, 2-component grip, with non-slip grip

FLT-SEC-H-T1-3C-440/25-FM - Type 1+2 combined lightning current and surge arrester



2907260

<https://www.phoenixcontact.com/us/products/2907260>

FLT-SEC-H-T1-440/25-P - Type 1 surge protection plug

2907261

<https://www.phoenixcontact.com/us/products/2907261>

Replacement plug for lightning current arresters from the FLASHTRAB SEC HYBRID 440 product range, for L-N and L-PEN paths.



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com