

IMPACT

TE Internal #: 2007820-2

120 Position, Mating Alignment, Polarization Mating Alignment Type, 12 Row, 10 Column, PCB Mount Header, IMPACT, High

Speed Backplane Connectors

View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > High Speed Backplane Connectors



Number of Positions: 120

Row-to-Row Spacing: 1.35 mm [.053 in]

Mating Alignment: With

Mating Alignment Type: Polarization

Number of Rows: 12

Features

Product Type Features

Signal Arrangement	Differential
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Shroud Style	Partially Shrouded
Configuration Features	
Number of Ground Positions	40
Number of Pairs	40
Stackable	No
Number of Signal Positions	80
Number of Positions	120

Electrical Characteristics

Number of Rows

Guide Location

Number of Columns

PCB Mount Orientation

Impedance	100 Ω
Operating Voltage	30 VAC

12

10

Vertical

Unguided



Signal Characteristics	
Number of Differential Pairs per Column	4
Data Rate	20 – 25 Gb/s
Body Features	
Primary Product Color	Black
Contact Features	
Contact Mating Area Length	4.9 mm[.193 in]
PCB Contact Termination Area Plating Material Thickness	.76 – 1.52 μm[30 – 60 μin]
Contact Layout	Inline
Contact Type	Pin
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Mating Area Plating Material Thickness	.76 μm[29.92 μin]
Contact Mating Area Plating Material	Gold
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Dual Beam
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
PCB Contact Termination Area Plating Material Contact Base Material	Tin Copper Alloy
Contact Base Material	Copper Alloy
Contact Base Material Contact Current Rating (Max)	Copper Alloy
Contact Base Material Contact Current Rating (Max) Termination Features	Copper Alloy .75 A
Contact Base Material Contact Current Rating (Max) Termination Features Termination Post & Tail Length	Copper Alloy .75 A 1.4 mm[.055 in]
Contact Base Material Contact Current Rating (Max) Termination Features Termination Post & Tail Length Termination Method to PCB	Copper Alloy .75 A 1.4 mm[.055 in]
Contact Base Material Contact Current Rating (Max) Termination Features Termination Post & Tail Length Termination Method to PCB Mechanical Attachment	Copper Alloy .75 A 1.4 mm[.055 in] Through Hole - Press-Fit
Contact Base Material Contact Current Rating (Max) Termination Features Termination Post & Tail Length Termination Method to PCB Mechanical Attachment Guide Hardware	Copper Alloy .75 A 1.4 mm[.055 in] Through Hole - Press-Fit Without
Contact Base Material Contact Current Rating (Max) Termination Features Termination Post & Tail Length Termination Method to PCB Mechanical Attachment Guide Hardware Mating Retention	Copper Alloy .75 A 1.4 mm[.055 in] Through Hole - Press-Fit Without Without
Contact Base Material Contact Current Rating (Max) Termination Features Termination Post & Tail Length Termination Method to PCB Mechanical Attachment Guide Hardware Mating Retention PCB Mount Retention	Copper Alloy .75 A 1.4 mm[.055 in] Through Hole - Press-Fit Without Without With
Contact Base Material Contact Current Rating (Max) Termination Features Termination Post & Tail Length Termination Method to PCB Mechanical Attachment Guide Hardware Mating Retention PCB Mount Retention Type	Copper Alloy .75 A 1.4 mm[.055 in] Through Hole - Press-Fit Without Without With Action/Compliant Tail
Contact Base Material Contact Current Rating (Max) Termination Features Termination Post & Tail Length Termination Method to PCB Mechanical Attachment Guide Hardware Mating Retention PCB Mount Retention PCB Mount Retention Type Mating Alignment	Copper Alloy .75 A 1.4 mm[.055 in] Through Hole - Press-Fit Without Without With Action/Compliant Tail With
Contact Current Rating (Max) Termination Features Termination Post & Tail Length Termination Method to PCB Mechanical Attachment Guide Hardware Mating Retention PCB Mount Retention PCB Mount Retention Type Mating Alignment Mating Alignment Type	Copper Alloy .75 A 1.4 mm[.055 in] Through Hole - Press-Fit Without Without With Action/Compliant Tail With Polarization



End Wall Location	Open
Housing Material	LCP - GF (Liquid Crystal Polymer)
Centerline (Pitch)	1.9 mm[.075 in]
Dimensions	
Connector Length	18.9 mm[.744 in]
Connector Height	11.95 mm[.47 in]
Connector Width	20.8 mm[.819 in]
PCB Thickness (Recommended)	1 mm
PCB Hole Diameter	.39 mm[.015 in]
Row-to-Row Spacing	1.35 mm[.053 in]
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Compatible With Approved Standards Products	CSA Certified, UL E28476
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Box & Tube, Package

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2007715-1 IMP100S,R,RA4P10C,LG,39



TE Part # 2007711-1 IMP100S,R,RA3P16C,UG,39



TE Part # 2007716-1 IMP100S,R,RA4P10C,RG,39



TE Part # 2007717-1 IMP100S,R,RA4P10C,UG,39



TE Part # 2007712-1 IMP100S,R,RA4P10C,LG,46




TE Part # 2007713-1 IMP100S,R,RA4P10C,RG,46



TE Part # 2007714-1 IMP100S,R,RA4P10C,UG,46

Also in the Series | IMPACT



Customers Also Bought





TE Part #1462042-3
IMC06GR=IM RELAY 140mW 12V 1CO



TE Dark #2 1202210.0

TE Part #2-1393210-0 T9AS1D12-5





TE Part #2007837-2 IMP100S,H,V4P16C,UG,LEW39,4.9



TE Part #2007839-2 IMP100S,H,V4P16C,UG,REW39,4.9



TE Part #2057439-2 IMP100S,H,V4P8C,RG,OEW39,4.9

TE Part #1SNA118618R0100 FEM12

TE Part #5-1892820-3
SQUE REL REC ASSY W/K,4ACP

Documents

Product Drawings

IMP100S,H,V4P10C,UG,OEW39,4.9

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2007820-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2007820-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2007820-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

120 Position, Mating Alignment, Polarization Mating Alignment Type, 12 Row, 10 Column, PCB Mount Header, IMPACT, High Speed Backplane Connectors



Application Specification

English

Agency Approvals

Agency Approval Document

English