

No Image Available

1674453-3

TE Internal Number: 1674453-3

Active

Universal Serial Bus (USB) Connectors



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- USB 2.0 Industry Standard
- Size = Standard
- A Series
- Receptacle
- Without Locking Feature

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)



[Add to My Part List](#)



[Request Sample](#)



[Find Similar Products](#)



[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [HARD TRAY ASSY USB CONNECTOR REC 3P](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Size = Standard
- [Series](#) = A
- Gender = Receptacle
- Number of Ports = 3
- Orientation = Flag

Mechanical Attachment:

- Mount Location = Top

Termination Features:

- Termination Method = Solder
- Tail Length (mm [in]) = 2.6 [0.102]

Body Features:

- Locking Feature = Without
- LED = Without
- [Panel Ground](#) = Without
- PCB Mount Retention Type = Straight Leg
- Shell Plating = Bright Tin
- Assembly Process Feature = Without Pick and Place Cover
- Locating Post(s) = Without
- Number of Positions = 4

Contact Features:

- Contact Termination Type = Through Hole
- [Contact Plating, Mating Area, Material](#) = Gold
- Contact Plating, Mating Area, Thickness (µm [µin]) = 0.762 [30]

Housing Features:

- [Housing Color](#) = Natural

Industry Standards:

- Industry Standard = USB 2.0
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- USB-IF Test ID Number (TID) = Not Submitted For Testing

Conditions for Usage:

- Applies To = Printed Circuit Board
- PCB Thickness, Recommended (mm [in]) = 1.00 [0.039]

Packaging Features:

- [Packaging Method](#) = Tray

Other:

- Brand = AMP

Corporate Information

[Who We Are](#)

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

Quick Links

[Check Distributor Inventory](#)

[Cross Reference](#)

[Find Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

Customer Support

[Email or Chat With Us](#)

[Find a Phone Number](#)

[Search Knowledge Base](#)

[Manage your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address

