

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Extruded heatsinks for lock-in retaining spring](#) » [SK 573 ...](#) » [SK 573](#)



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
 - Standard extruded heatsinks
 - [Extruded heatsinks for lock-in retaining spring](#)
 - Extruded heatsinks for PCB mounting
 - Extruded heatsinks for DC/DC converter
 - Retaining springs for transistors
 - U-Extruded heatsinks
 - Die-cast heatsinks
 - Fin coolers
 - Fluid coolers
 - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- Heatsinks and active heatsinks for processors
- Board Level heatsinks
- Cooling aggregates
- Accessories for electronic components
- **Cases f.case**
- **Connectors f.con**

Extruded heatsinks for lock-in retaining spring


SK 573 ...

SK 573 75 AL

25 x 30 mm, for THFU 1-3+6+7, profile threads

Data sheet

add to request



Features

Technical Drawing

Service

Accessories / related products

width B	25 mm
height	30 mm
plate thickness	8 mm
length	75 mm
thermal resistance R_{th}	7.2 - 3.4 K/W
surface	raw degreased aluminium