

Catalog No. F2021

Description: "INS PP FERRULE 20, .5 MM2, LG .531"

UPC No 786210339863

Home > Connectivity & Grounding > Sta-Kon > Electrical terminals

Polypropylene-Insulated Ferrule, Total Length .531 Inches/13.5mm, Pin Length .315 Inches/8mm, Pin Diameter .043 Inches/1.1mm, Base Diameter .098 Inches/2.5mm, Wire Range 20 AWG/.5mm2, Color White, Copper, Tin Plated



Representative Image

Descriptors

Category	Electrical terminals
Type	Polypropylene Insulated Ferrule
Special Features	Ferrules ensure reliable electrical connections when terminating conductors in screw clamp terminal blocks.

Specifications

Material	Copper
Color	White

Classifications

Brand Name	Sta-Kon
------------	---------

Dimensions

Wire Size	20 AWG
-----------	--------

Compliance and Certifications

RoHS	RoHS3 Compliant
REACH SVHC	REACH 223 Compliant
TSCA	TSCA Section 6(h) Compliant

ETIM	EC000005 Cable end sleeve
Construction type	Standard
Nominal cross section	0.5 mm ²
Insulated	Y
Material insulation	Polypropylene
Colour	White
Material	Copper
Surface protection	Tinned

ETIM	EC000005 Cable end sleeve
With identification flag	N
Reel packaging	N
AWG size	20