SST-30-03/226 ACTIVE

RAYCHEM | RAYCHEM SST/SST-FR

TE Internal #: CB5309-000

Black, 3:1, Single Wall Tubing, Shrinks To 2.54 mm [.1 in], Irradiated Modified Polyolefin, 7.62 mm [.3 in] Inner Diameter, RAYCHEM SST

/SST-FR

View on TE.com >



Heat Shrink Tubing > SST Heat Shrink Tubing



Primary Product Color: Black

Wall Type: Single Wall

Expanded Inside Diameter (Min): 7.62 mm [.3 in] Recovered Inside Diameter (Max): 2.54 mm [.1 in]

Shrink Ratio: 3:1

All SST Heat Shrink Tubing (63)

Features

Product Type Features	
Wall Type	Single Wall
Electrical Characteristics	
Operating Voltage (Max)	.6 kV
Body Features	
Fluid Type	Aviation Fuel, De-Icing Fluid, Hydraulic Fluid, Lubricating Oil, Water
Primary Product Color	Black
Shrink Ratio	3:1
Primary Product Material	Irradiated Modified Polyolefin
Flexibility	Semi-Rigid
Dimensions	
Recovered Wall Thickness (Tolerance)	1.78 mm[.07 in]
Product Length	762 mm[30 in]
Expanded Inside Diameter (Min)	7.62 mm[.3 in]
Recovered Inside Diameter (Max)	2.54 mm[.1 in]
Tubing Size Range	2.54 – 7.62 mm[.1 – .3 in]



Usage Conditions

Shrink Temperature (Min)	90 °C
Resistance Properties	Moisture
Tubing Flammability Type	Non-Flame-Retardant
Operating Temperature Range	-55 – 110 °C
Recovery Temperature	121 °C

Operation/Application

Mechanical Resistance	Abrasion, Fluids, Moisture

Product Availability

Applicable Region	Global	

Packaging Features

Packaging Method	Вох	

Other

Meets Low Outgassing Requirements	No
Product Source	Czech Republic

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach


Compatible Parts







Also in the Series | RAYCHEM SST/SST-FR



Customers Also Bought



TE Part #207463-1 CRIMP SNAP RCPT ASSY,SZ 3



TE Part #1827587-2 DYNAMIC D1000 REC CONT M AU 0.38um L/P



TE Part #5748677-2 PLTD PLST CBL CLMP KIT,SZ 2















Documents

Product Drawings

SST-30-03/226

English

Datasheets & Catalog Pages

Measuring_Single_Wall_Tubing

English

SST and SST-FR Pages from 9-1773447-9

English

Selecting_Correct_Tubing_1216

English

Product Specifications

Application Specification

English