

FEMALE PLUG M8 90° ANGLED TO MALE PLUG M8 90° ANGLED WSOR CABLES

LENGTH + TOLERANCE (SEE SHEET 2+3)

"BRAD" LOGO ONLY ON ONE
SIDE OF THE OVERMOLD

NOTES:

1. PRODUCT SPECIFICATION:

RATED VOLTAGE:

3 contacts 60V AC/DC

4 and 5 contacts 30V AC/DC

CURRENT RATING: 3, 4, 5 contacts 3A

PROTECTION CLASS: IP 67

TEMPERATURE: -25°C / +80°C

2. PACKAGING: THE CORDSETS ARE

PACKED IN PLASTIC BAGS AND

DELIVERED IN CARTON BOXES

3. SAFETY: INSTALLATION, MOUNTING,

AND MAINTENANCE OF THE

PRODUCT MAY ONLY BE CARRIED

OUT BY A QUALIFIED

ELECTRICIAN

4. INSULATION RESISTANCE: $10^8 \Omega \cdot \text{M}$

5. MATING CYCLES: MAX 100

CONTACT POSITION FRONT VIEW:

[illegible]

CODING ACCORDING TO IEC 61076-2-104

DOCUMENT STATUS	P1	RELEASE DATE	2024/07/02	09:18:41
-----------------	----	--------------	------------	----------

FORMAT: master-tb-prod-A3
REVISION: J1
DATE: 2021/05/01

(BACK VIEW)

SCALE 1:1


FOR OPTIONS SEE NUMERICAL CODE ON SHEET 2

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH / COLOR
1	3 / 4 / 5	CONTACT M8 FEMALE	BRONZE	SELECTIVE Au OVER Ni
2	1	O-RING	FKM	RED
3	1	INSERT FEMALE	TPU	BLACK
4	1	COUPLING NUT M8 FEMALE SW9	BRASS	NICKEL
5	-	OVERMOLD	TPU	BLACK
6	-	CABLE	SEE SHEET 2	---
7	1	LABEL	VINYL	YELLOW
8	1	COUPLING NUT M8 MALE SW9	BRASS	NICKEL
9	1	SLEEVE	BRASS	NICKEL
10	3 / 4 / 5	CONTACT M8 MALE	Cu-ALLOY	SELECTIVE Au OVER Ni
11	1	INSERT MALE	TPU	BLACK
12	2	I/D CARRIER	PVC	---

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																
$\overline{E_A} = 0$ $\overline{E_C} = 0$ $\overline{E_E} = 0$ DIVISIONAL SYMBOLS	DIMENSION UNITS		SCALE		CURRENT REV DESC: AS PER THE PCN-513749 CHANGED DIMENSIONING STYLE OF OVERALL LENGTH TO "END TO END". ADDED NOTES 4 & 5. SORTED PART LIST USING CABLE TYPES ON SHEET 3				molex CSE M8 M8 XP XC FE RA WSOR MA RA XM								
	mm		2:1														
	GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 789428 DRWN: AKABADI 2023/08/24 CHK'D: RSILLER 2024/07/02 APPR: RSILLER 2024/07/02 INITIAL REVISION: DRWN: RSCHIEBER 2018/11/19 APPR: RSILLER 2018/12/10										PRODUCT CUSTOMER DRAWING		
	ANGULAR TOL ± 1.0°																
	4 PLACES		±														
	3 PLACES		±														
	2 PLACES		± 0.05														
1 PLACE		± 0.3															
0 PLACES		± 0.5															
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER			
						A3-SIZE		120087		SEE PART LIST		GENERAL MARKET		1 OF 3			
										1200878769		PSD		000		B	

ENGINEERING NO. - NUMERICAL CODE (Available parts see PART LIST table. Other parts available upon request).

OPTIONS



44=Nano-Change
M8x1
Double ended

Poles:
3=3 Contacts
4=4 Contacts
5=5 Contacts

Heads style:
032=Plug Female 90°
to Plug Male 90°


Cable type: See Table

Units:
M=Meter
C=Centimeter

Length
Examples:
005=0.5 unit
010=1 unit
100=10 unit

Overmold color:
Blank (Standard)=Black

H= 2 pcs. of
I/D Carrier PVC Transparent



CABLE INFORMATION (for more information see Cable Data Sheet)

CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAG CHAIN: TEMP. / BENDING RADIUS	DRAG CHAIN	CABLE PRODUCT SPECIFICATION	CABLE SPEC. DRAWING
B41	3 / 4 / 5	0.25mm²	TPU Black	UL 21215/758	C22.2 I/II A/B 80°/600V	-40°C to +90°C 5xO.D.	-25°C to +80°C 7.5xO.D.	-5°C to +60°C 7.5xO.D.	up to 5 000 000 cycles at temp 20°C	1552200001	SD-120209-001

CABLE LENGTH TOLERANCES

LENGTH	TOLERANCE
0m-1m	+40 mm
>1m-5m	+60 mm
>5m-10m	+80 mm
>10m-20m	+140 mm
>20m-30m	+160 mm
>30m	+1% length

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																	
FUNCTIONAL SYMBOLS	DIMENSION UNITS		SCALE		CURRENT REV DESC: AS PER THE PCN-513749 CHANGED DIMENSIONING STYLE OF OVERALL LENGTH TO "END TO END". ADDED NOTES 4 & 5. SORTED PART LIST USING CABLE TYPES ON SHEET 3					molex CSE M8 M8 XP XC FE RA WSOR MA RA XM							
	mm		2:1														
	GENERAL TOLERANCES (UNLESS SPECIFIED)																
	ANGULAR TOL ± 1.0 °																
DIVISIONAL SYMBOLS	4 PLACES		±		EC NO: 789428					2023/08/24 2024/07/02 2024/07/02							
	3 PLACES		±		DRWN: AKABADI												
	2 PLACES		± 0.05		CHK'D: RSILLER												
	1 PLACE		± 0.3		APPR: RSILLER					PRODUCT CUSTOMER DRAWING							
	0 PLACES		± 0.5		INITIAL REVISION:					DOCUMENT NUMBER		DOC TYPE		DOC PART		REVISION	
					DRWN: RSCHIEBER					1200878769		PSD		000		B	
				APPR: RSILLER					2018/11/19 2018/12/10								
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION			DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER		
							A3-SIZE		120087		SEE PART LIST		GENERAL MARKET		2 OF 3		

