

M12 Connector

TE Internal #: T4141512041-000

Wire-to-Panel, 4 Position, Sealable, Wire & Cable, Signal, Panel Mount, Reverse Gender, Nickel, M12 Connector, Standard Circular

Connectors

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors > M12 Panel Mount PCB











Connector System: Wire-to-Panel

Connector Mounting Type: Panel Mount

Number of Positions: 4

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

All M12 Panel Mount PCB (111)

Features

Product Type Features

| Product Type | Connector Assembly |
|-----------------------------------|----------------------|
| | |
| Accessory Color | Black |
| Assembly Requirement | Factory Assembled |
| Assembly Type | Electrical Connector |
| Circular Connector Shell Type | Metal-Shell |
| Connector Product Type | Connector Assembly |
| Connector System | Wire-to-Panel |
| Sealable | Yes |
| Connector & Contact Terminates To | Wire & Cable |
| Circular Connector Type | Receptacle |
| Shell Type | Metal |

Configuration Features

| Keying & Polarized Position Locations | D | |
|---------------------------------------|---|--|



| Recying | | |
|--|---|---------------------------|
| Number of Positions 4 Number of Power Positions 0 Number of Signal Positions 4 Contacts Preloaded Yes Electrical Characteristics Operating Voltage 250 VAC Body Features Peripheral Seal Material Silicone Environmental Protection IP67 O-Ring Material Silicone Environmental Protection Iype Elastomer Sealed Shell Plating Material Nickel Shell Plating Material Copper Alloy Croular Connector Insulation Material Type Polyamide GF Illermelically Sealed Yes Contact Features Contact Current Rating (Max) 4 A Reverse Gender Yes Croular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operation/Application | Factory Installed Backshell | No |
| Number of Power Positions 4 Contacts Preloaded Yes Electrical Characteristics Operating Voltage 250 VAC Body Features Peripheral Seal Material Silicone Environmental Protection IP6/ O-Ring Material Silicone Environmental Protection IP6/ O-Ring Material Silicone Environmental Protection Ippe Elastomer Sealed Shell Plating Material Nickel Shell Blase Material Copper Alloy Circular Connector Insulation Material Type Polyamide GIF Hermetically Sealed Yes Contact Features Contact Features Contact Current Rating (Max) 4 A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operation/Application | Keying | D |
| Number of Signal Positions 4 Contacts Preloaded Yes Electrical Characteristics Operating Voltage 250 VAC Body Features Peripheral Seal Material Silicone Environmental Protection IP6/ O-Ring Material Silicone Environmental Protection Iype Elastomer Sealed Shell Plating Material Nickel Shell Plating Material Copper Alloy Circular Connector Insulation Material Type Polyamide GF Hometically Sealed Yes Contact Current Rating (Max) 4 A Reverse Gender Yes Contact Current Rating (Max) 4 A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Scaling Level IP67 Operation/Application | Number of Positions | 4 |
| Contacts Preloaded Yes Electrical Characteristics Operating Voltage 250 VAC Body Features Peripheral Seal Material Silicone Environmental Protection IP67 O Ring Material Silicone Environmental Protection Vickel Silicone Environmental Protection Type Elastomer Scaled Shell Plating Material Nickel Capper Alloy Circular Cannector Insulation Material Type Polyamide GF Hermetically Sealed Yes Contact Features Contact Features Contact Current Rating (Max) 4 A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Meting Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operation/Application | Number of Power Positions | 0 |
| Electrical Characteristics Operating Voltage 250 VAC Body Features Peripheral Seal Material Silicone Environmental Protection IP67 O-Ring Material Silicone Environmental Protection IP67 O-Ring Material Silicone Environmental Protection Type Elastomer Sealed Shell Plating Material Nickel Shell Plating Material Copper Alloy Circular Connector Insulation Material Type Polyamide Gl' Hermotically Sealed Yes Contact Features Contact Features Contact Current Rating (Max) 4 A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operating Temperature Range -40 –85 °C[-40 – 185 °T] Operating Temperature Range -40 –85 °C[-40 – 185 °T] | Number of Signal Positions | 4 |
| Operating Voltage 250 VAC Body Features Peripheral Seal Material Silicone Environmental Protection IP67 O Ring Material Silicone Finatomental Protection Type Flastomer Sealed Shell Plating Material Nickel Shell Base Material Copper Alloy Circular Connector Insulation Material Type Polyamide GF Hermetically Sealed Yes Contact Features Contact Features Contact Current Rating (Max) 4 A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operating Temperature Range -40 –85 °C[-40 – 185 °F] Operating Temperature Range Operation/Application | Contacts Preloaded | Yes |
| Body Features Peripheral Seal Material Silicone Environmental Protection IP67 O-Ring Material Silicone Environmental Protection Type Flastomer Sealed Shell Plating Material Nickel Shell Base Material Copper Alloy Gircular Connector Insulation Material Type Polyamide GI Hernetically Sealed Yes Contact Features Contact Features Contact Current Rating (Max) 4 A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operation/Application | Electrical Characteristics | |
| Peripheral Seal Material Environmental Protection O Ring Material Silicone Environmental Protection Type Elastomer Sealed Shell Plating Material Nickel Shell Base Material Copper Alloy Circular Connector Insulation Material Type Hermetically Sealed Yes Contact Features Contact Current Rating (Max) A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level Operation/Application | Operating Voltage | 250 VAC |
| Environmental Protection O Ring Material Silicone Environmental Protection Type Elastomer Sealed Shell Plating Material Nickel Shell Base Material Copper Alloy Circular Connector Insulation Material Type Polyamide GF Hermetically Sealed Yes Contact Features Contact Current Rating (Max) Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Housing Features Circular Connector Shell Size Usage Conditions IP Water Sealing Level Operation/Application | Body Features | |
| C-Ring Material Environmental Protection Type Elastomer Sealed Shell Plating Material Nickel Shell Base Material Copper Alloy Circular Connector Insulation Material Type Polyamide GF Hermetically Sealed Yes Contact Features Contact Current Rating (Max) Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code Mating Alignment Type Keyed Housing Features Circular Connector Shell Size Usage Conditions IP Water Sealing Level Operation/Application | Peripheral Seal Material | Silicone |
| Environmental Protection Type Shell Plating Material Shell Base Material Copper Alloy Circular Connector Insulation Material Type Polyamide GF Hermetically Sealed Yes Contact Features Contact Current Rating (Max) Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size Usage Conditions IP Water Sealing Level Operating Temperature Range Operation/Application | Environmental Protection | IP67 |
| Shell Plating Material Copper Alloy Circular Connector Insulation Material Type Polyamide GF Hermetically Sealed Yes Contact Features Contact Current Rating (Max) 4 A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operation/Application | O-Ring Material | Silicone |
| Shell Base Material Copper Alloy Circular Connector Insulation Material Type Polyamide GF Hermetically Sealed Yes Contact Features Contact Current Rating (Max) 4A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operation/Application | Environmental Protection Type | Elastomer Sealed |
| Circular Connector Insulation Material Type Hermetically Sealed Yes Contact Features Contact Current Rating (Max) Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level Operating Temperature Range Operation/Application | Shell Plating Material | Nickel |
| Contact Features Contact Current Rating (Max) 4 A Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operation/Application | Shell Base Material | Copper Alloy |
| Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level Operating Temperature Range Operation/Application | Circular Connector Insulation Material Type | Polyamide GF |
| Contact Current Rating (Max) Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application | Hermetically Sealed | Yes |
| Reverse Gender Yes Circular Connector Contact Type Socket Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application | Contact Features | |
| Circular Connector Contact Type Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level Operating Temperature Range Operation/Application | Contact Current Rating (Max) | 4 A |
| Mechanical Attachment Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application | Reverse Gender | Yes |
| Connector Mounting Type Panel Mount Polarization Code D Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operation/Application | Circular Connector Contact Type | Socket |
| Polarization Code Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level Operating Temperature Range Operation/Application | Mechanical Attachment | |
| Mating Alignment Type Keyed Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application | Connector Mounting Type | Panel Mount |
| Housing Features Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application | Polarization Code | D |
| Circular Connector Shell Size 18 Usage Conditions IP Water Sealing Level IP67 Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application | Mating Alignment Type | Keyed |
| Usage Conditions IP Water Sealing Level Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application | Housing Features | |
| IP Water Sealing Level Operating Temperature Range -40 - 85 °C[-40 - 185 °F] Operation/Application | Circular Connector Shell Size | 18 |
| Operating Temperature Range -40 – 85 °C[-40 – 185 °F] Operation/Application | Usage Conditions | |
| Operation/Application | IP Water Sealing Level | IP67 |
| | Operating Temperature Range | -40 - 85 °C[-40 - 185 °F] |
| Circuit Application Signal | Operation/Application | |
| | Circuit Application | Signal |



| Shielded | No |
|------------------------|---------|
| Industry Standards | |
| UL Flammability Rating | UL 94HB |
| Packaging Features | |
| Packaging Quantity | 1 |
| Other | |
| Field Serviceable | No |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts








Also in the Series | M12 Connector

PG7,GOLD











Customers Also Bought

















Documents

Product Drawings

M12,REAR MOUNTING,FEMALE,D CODE,4P

English

CAD Files

Customer View Model

ENG_CVM_CVM_T4141512041-000_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4141512041-000_B.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_T4141512041-000_B.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

Product Specifications

Application Specification

English

Agency Approvals

UL

English