




- Note:
- 1.Material:
- 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
 - 1.2 Contact: copper alloy,t=0.20mm
 - 1.3 Shell: copper alloy,t=0.25mm
- 2.Specification:
- 2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.
 - 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - 2.3 Contact resistance: 30 mΩ Max.
 - 2.4 Insulation resistance: 100 MΩ Min.
 - 2.5 Total mating force: 3.57 Kgf Max.
 - 2.6 Total unmating force: 1.0 Kgf Min
 - 2.7 Temperature range: -30°C~80°C

产品图		深圳市精拓金电子有限公司							
PRODUCT CHART DWG									
公差一览表		单位	MM	制图	尹先华	制图料号	920-D62A2021S10108		
TOLERANCE UNLESS OTHERWISE		UNITS		DRAWING		PRODUCT PART NO.			
X.	±0.30	X.	±5.°	比例	郭治富	产品名称	MICRO 5S B型两脚贴板无边有柱SMT端子		
.X	±0.25	.X	±2.°	SCALE	核准	PRODUCT NO.	加长0.75		
.XX	±0.15	.XX	±1.°	日期	黄国荣	角法	版本	AO	
.XXX	±0.10	.XXX	±0.5°	DATE	2021-04-16	APPD	VIEW	VER	