








REV.	ECN NO.	DATE	SIGN	DESCRIPTION
F	LE31190025	2011/06/23	Tao-Cheng	Change Connector Material
G	LEN1350083	2013/04/29	Ruru	Modify Seals Cable OD
H	LEN15A0030	2015/09/21	Ruru	Change Logo



Pin Assignments
Front View



- Note:**
- * **QC** Important Dimensions.
 - * Waterproof Rate: IP67
 - * Connector: M-PPE 540Z, Black
 - * Pin: Copper Alloy, Gold Plated
 - * O-Ring 1: Viton, Green
 - * O-Ring 2: EPDM, Black
 - * Holder: Nylon+GF, Black
 - * Clamp Ring: Nylon 66, Black
 - * Gasket: EPDM, Black
 - * Sealing Nut: Nylon 66, Black
 - * Nut: Nylon+GF, Black
 - * Seals For Cable OD: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$
 - * Temperature Range: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

UNIT:mm		TITLE M12 Screw In Female Conn A-Coded		ITEM NO 12P-04BFFB-SL7001		DRAWN BY Ruru		DATE 2015-09-21	
TOLERANCE .X ± 0.25 .XX ± 0.1 .XXX ± 0.05 ANGLES $\pm 1^{\circ}$		SCALE 1:1	SIZE A4	SHEET 1	OF 1	DWG NO 12P-04BFFB-SL7001		CHECKED BY Rita	
REV. H		WC-REV. B.2		QC: Inspection item		CUSTOMER ALTW		APPROVED BY Lion	
								DATE 2015-09-21	

Amphenol LTW
安費諾亮泰企業股份有限公司

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[V01C-E-M50C-2-N](#) [V06G-E-M50C-4-N](#) [V01C-E-M50C-4-N](#) [V06G-E-M50C-2-N](#) [V01C-E-M63C-6-N](#) [V06G-E-M63C-6-N](#) [V03B-E-N-40](#) [V03B-E-N-32](#) [V01C-E-M63C-8-N](#) [V06G-E-M63C-8-N](#)