

TITLE:

☐

⌘

Gold over Nickel underplate on contact area,

lin over Copper underplate on PCB tails,
(See chart for thickness)

Operating voltage: 125 VAC max

Current rating: 1.5 Amps max

Contact resistance: 20 mohms max

Insulation resistance: 1000 Mohms min @ 500 VDC
Dielectric withstanding voltage: 1000 VAC for 1 minute

Temperature Rating:

Operating temperature: -40°C to $+85^{\circ}\text{C}$

Environmental:

Lead free, RoHS compliant.

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]			
TOLERANCES: EXCEPT AS NOTED			
INCHES		HOLES	
.X	± .10	ØX	± .10
.XX	± .020	ØXX	± .015
.XXX	± .015	ØXXX	± .010
APPROVALS		DATE	
DRAWN	SS	10/4/04	
CHECKED			
APPROVED			
TITLE			
MODULAR TELEPHONE JACK, 8P8C			
RIGHT ANGLE, PCB			
ADAM TECH 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710			
SIZE	PART NO.	REV.	
X	MTJ-88GX1	D	
REF:	S00005C	SCALE:	NTS
SHEET 1		OF 1	

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

MODULAR TELEPHONE JACK, 8P8C
RIGHT ANGLE, PCB

SIZE	PART NO.
------	----------

MTJ-88GX1

REF: S00005C

SCALE: N

SHEET 1 OF 1