

# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

ECOR-2 relay base, for industrial relays with four changeover contacts, bolt connection, for mounting on NS 35/7,5



## Commercial data

Item number	2908214
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	C463
Product key	CKF313
GTIN	4055626289144
Weight per piece (including packing)	55.07 g
Weight per piece (excluding packing)	50.5 g
Customs tariff number	85366990
Country of origin	CN

# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## Technical data

### Product properties

Product type	Relay socket
Product family	ESSENTIAL edition

### Data management status

Article revision	01
------------------	----

### Electrical properties

Nominal voltage $U_N$	250 V AC/DC
Nominal current $I_N$	5 A

### Connection data

#### Input side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) 2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)
Conductor cross section flexible	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) 2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)

#### Output side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) 2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)
Conductor cross section flexible	2x 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) 2x 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)

### Dimensions

Width	29.8 mm
Height	64.9 mm
Depth Retaining bracket	63 mm (ECOR-RHM-2)

### Material specifications

Color	traffic grey B (RAL 7043)
-------	---------------------------

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C

# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## Mounting

Mounting type	DIN rail mounting
Mounting position	any

# ECOR-2-BSC2-RT/4X21 - Relay base




2908214


<https://www.phoenixcontact.com/us/products/2908214>

## Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2908214>




**CSA**  
Approval ID: 255476



**cUL Recognized**  
Approval ID: FILE E 113228



**UL Recognized**  
Approval ID: FILE E 113228



**EAC**  
Approval ID: RU C-DE.\*\*08.B.01419

**cULus Recognized**

# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## Classifications

### ECLASS

ECLASS-11.0	27371603
ECLASS-12.0	27371603
ECLASS-13.0	27371603

### ETIM

ETIM 9.0	EC001456
----------	----------

### UNSPSC

UNSPSC 21.0	39122300
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## Mandatory accessories

### REL-IR-BL/L- 12DC/4X21 - Single relay

1109557

<https://www.phoenixcontact.com/us/products/1109557>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 12 V DC

---

### REL-IR-BL- 24DC/4X21 - Single relay

1032521

<https://www.phoenixcontact.com/us/products/1032521>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, polarity A1+, A2-, input voltage: 24 V DC

# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## REL-IR-BL/L- 24DC/4X21 - Single relay

1032527

<https://www.phoenixcontact.com/us/products/1032527>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V DC

---

## REL-IR-BL/L- 48DC/4X21 - Single relay

1109558

<https://www.phoenixcontact.com/us/products/1109558>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 48 V DC



# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## REL-IR-BL/L-110DC/4X21 - Single relay

1109560

<https://www.phoenixcontact.com/us/products/1109560>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 110 V DC

---

## REL-IR-BL/L-125DC/4X21 - Single relay

1109561

<https://www.phoenixcontact.com/us/products/1109561>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 125 V DC

# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## REL-IR-BL/L-220DC/4X21 - Single relay

1109562

<https://www.phoenixcontact.com/us/products/1109562>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 220 V DC

---

## REL-IR-BL/L- 24AC/4X21 - Single relay

1109563

<https://www.phoenixcontact.com/us/products/1109563>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V AC

# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## REL-IR-BL/L-115AC/4X21 - Single relay

1109564

<https://www.phoenixcontact.com/us/products/1109564>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 115 V AC

---

## REL-IR-BL-230AC/4X21 - Single relay

1032529

<https://www.phoenixcontact.com/us/products/1032529>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, input voltage: 230 V AC

# ECOR-2-BSC2-RT/4X21 - Relay base

2908214

<https://www.phoenixcontact.com/us/products/2908214>



## REL-IR-BL/L-230AC/4X21 - Single relay

1032531

<https://www.phoenixcontact.com/us/products/1032531>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 230 V AC

---

## Accessories

### DB 50- 90 BU - Wire bridge

2821180

<https://www.phoenixcontact.com/us/products/2821180>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm<sup>2</sup>, loop length: 90 mm, ferrule length: 8 mm, color: blue



# ECOR-2-BSC2-RT/4X21 - Relay base



2908214

<https://www.phoenixcontact.com/us/products/2908214>

## DB 50- 90 BK - Wire bridge

2820916

<https://www.phoenixcontact.com/us/products/2820916>

Flexible wire loop bridge, 50-pos., conductor cross-section:  $0.5 \text{ mm}^2$ , loop length: 90 mm, ferrule length: 8 mm, color: black



---

## DB 50- 90 GY - Wire bridge

2820929

<https://www.phoenixcontact.com/us/products/2820929>

Flexible wire loop bridge, 50-pos., conductor cross-section:  $0.5 \text{ mm}^2$ , loop length: 90 mm, ferrule length: 8 mm, color: gray



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)