

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ ROCKER SWITCHES

Rocker switches

SERIES 1900 - SMALLEST SINGLE-POLE ROCKER SWITCHES - TO 6 (2) A 250 V AC

◀ Show previous product

Show next product ▶

1901.1106

Drawing

Similar to original
product

→ Print data sheet

Product number	1901.1106
Actuator color / printing	
Miscellaneous	rocker marking silver
Switching function	ON / OFF switch (SPST)
Number of poles	1-pole
connections	Quick-connect terminal, 4.8
Mechanical life endurance	75E3
Rating IEC	6 (2) A 250 V AC 4 (1) A 250 V AC 5E4
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +85 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, white
Housing description	PA, white
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 80 N
Operating force	2 - 5 N
Approval marks	cULus / ENEC 05
Suitable for appliances of protection class	I