

This document was generated on 11/13/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0353171420

Status: Active

Overview: Mini-Fit Jr. Power Connectors

Description: 4.20mm Pitch Mini-Fit Header, Dual Row, Vertical, 14 Circuits, PA Polyamide (Nylon)

6/6 94V-2, White

Documents:

<u>Drawing (PDF)</u> <u>Packaging Specification PK-35317-001-001 (PDF)</u>

Product Specification PS-35317-001-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>35317</u>

Application Power, Wire-to-Board

Comments Current = 13A max. per circuit when header is mated to

a receptacle loaded with <u>45750 Mini-Fit Plus HCS Crimp</u> Terminal Crimped to 16 AWG wire., See Molex product specification PS-45750-001 for additional current de-

rating information.

Overview <u>Mini-Fit Jr. Power Connectors</u>

Product Name Mini-Fit


UPC 756054272503

Physical

Breakaway No Circuits (Loaded) 14 Circuits (maximum) 14 Color - Resin Natural Durability (mating cycles max) 30 First Mate / Last Break No Flammability 94V-2 Glow-Wire Capable No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nvlon Net Weight 2.568/g Number of Rows Orientation Vertical

PC Tail Length 3.50mm **PCB** Locator Yes **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Bag Pitch - Mating Interface 4.20mm Polarized to PCB No Shrouded Partial Stackable No Surface Mount Compatible (SMC) No

Temperature Range - Operating -40° to +105°C
Termination Interface: Style Through Hole



EU ELV

Not Relevant

EU RoHS China RoHS

CompliantREACH SVHC

Not Contained Per

-ED/01/2018 (15 January 2018)

Halogen-Free

Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

35317 Series

Mates With

5557 Mini-Fit Jr. Receptacle Housing

Electrical

Current - Maximum per Contact 13.0A Voltage - Maximum 250V

Material Info

Reference - Drawing Numbers

Packaging Specification PK-35317-001-001
Product Specification PS-35317-001-001
Sales Drawing 353171020-000

This document was generated on 11/13/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION