

Coaxial Cable Connector 11_4310-50-5-X1/003_-

Description

Straight cable plug

Interface standards
IEC 61169-54



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	12 GHz

Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0265 kg

Environmental Data

Operating temperature	-55 °C to 90 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	NBR (Nitrile butadiene rubber)	

Related Documents

Outline drawing	DOU-00259038
Catalogue drawing	DCA-00264957
Assembly instruction	DOC-0000460547

Ordering Information

Bulk 100 pcs package	11_4310-50-5-X1/003_-H
Single package	11_4310-50-5-X1/003_-E

Additional Information

Suitable cables	SUCOFORM_250-01_FEP, EZ_250_M17
-----------------	---------------------------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

[11_4310-50-5-X1/003_-E](#) [11_4310-50-5-X1/003_-H](#)