



SECTION P-P

N= Number of poles

Dim A	Nx10.16+17.76	Poles	Tolerance
Dim B	Nx10.16-0.16	2P-4P	±0.25
Dim C	(N-1)x10.16+20.32	5P-7P	±0.30
Dim D	(N-1)x10.16	8P-10P	±0.35
		11P-12P	±0.45

SIGN	DATE	DESCRIPTION	APPROVER
△	2010.05.31	Add cULus standard	Jacke
△	2011.07.04	The Tolerance is changed	Aaron
△	2011.07.04	Remove the "cULus" mark	Aaron
△	2011.12.15	Screw is changed from M4 to M4.5	Aaron

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item a Terminal body:Thermoplastic (UL94V-0)
- Item b Terminal cover:Thermoplastic (UL94V-0)
- Item c Terminal screw:Steel Zinc plating "-" slot type
- Item d Clamp:Brass, Ni plated
- Item e Male contact pin:Copper Gold plated
- Item f With flange nut:Steel Zinc plating M3

Electrical cULus / IEC

- Voltage rating: 300VAC / 1000VAC
- Current rating: 55A / 76A
- Solid wire: 6-20 / 0.5-16mm²
- Stranded wire: 6-20 / 0.5-16mm²
- Torque: 18 Lb-In / 2.0 N.m
- △ ● Screw: M4.5
- Wire strip length: 13-14mm
- Withstanding Voltage: 1.6KV / 8KV
- Operating temperature: -40°C to +115°C
- △ △ ● Safety Approval:
- Critical dimension:▽

PART NO. KK xx 61 x 3 xxxx G

No. OF POLES
02 2 CONTACTS
03 3 CONTACTS
...
12 12 CONTACTS

Color

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)
- 9 White(RAL1102)
- C Green(RAL6018/U)

G: Pb<40000ppm

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request. please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	KK 10.16 Series 2p-12p (W/F nut type)					
PART NO.	KKxx61x3xxxxG			DWG NO.	8KK0101	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
		Aaron 2011.12.15	Kind 2008.11.1		UNIT: mm	X. ±0.50
					SCALE: NONE	X.X ±0.30
					SHEET: 01/01	X.XX ±0.10
					REV.: D	X° ±1°

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[KK0261530000G](#) [KK0361530000G](#) [KK0461530000G](#) [KK0561530000G](#) [KK0661530000G](#) [KK0761530000G](#)
[KK0861530000G](#) [KK0961530000G](#) [KK1061530000G](#) [KK1161530000G](#) [KK1261530000G](#)