




Connectors > D-Shaped Connectors > D-Sub Connectors > IDC D-Sub Connectors > IDC D-Sub: Plug Assembly, Low Profile, Signal, 2.77 mm



Connector & Housing Type: **Plug**

Solid Wire Size: **28 – 26 AWG**

Shielded: **No**

Connector System: **Cable-to-Cable**

[All IDC D-Sub: Plug Assembly, Low Profile, Signal, 2.77 mm \(17\)](#)

Features

Product Type Features

Shell Material Configuration	Front Metal Shell
Ground Feature Type	Grounding Indents
Connector & Housing Type	Plug
Connector System	Cable-to-Cable
Connector Product Type	Connector Assembly
Connector Shell Size	5
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	50
Number of Rows	3
Compatible With Wire & Cable Type	Ribbon Cable

Body Features

Ribbon Cable Centerline Spacing	1.27 mm[.05 in]
---------------------------------	-----------------



Mating Retention Feature Material	Steel
Shell Plating Finish	Bright
Cable Exit Angle	180°
Shell Plating Material	Tin
Connector Profile	Low

Contact Features

Contact Options	Installed
Contact Type	Pin
Wire Contact Termination Area Plating Material	Tin
	30 µin
Contact Mating Area Plating Material	Gold, Gold Flash
Contact Underplating Material	Palladium Nickel
Contact Base Material	Phosphor Bronze
Contact Size	Size 20
Contact Current Rating (Max)	1.25 A

Termination Features

Termination Method to Wire & Cable	Insulation Displacement (IDC)
------------------------------------	-------------------------------

Mechanical Attachment

Mating Retention Feature Plating Material	Zinc
Mating Retention	With
Mating Retention Type	Threaded Insert, 4-40 UNC
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Shell Material	Steel
Housing Material	Thermoplastic
Centerline (Pitch)	2.77 mm[.054 in]

Dimensions

Accepts Cable Insulation Diameter Range	.81 – .97 mm[.032 – .038 in]
Solid Wire Size	28 – 26 AWG
Wire Size	.08 – .15 mm²

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------



Operation/Application

Circuit Application	Signal
Shielded	No

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	32
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts






TE Part # 1658606-1
50 POS HDF RCPT, MS, LEAD FREE




TE Part # CAT-025-DRAVS5277
D-Sub Receptacle Assembly: Vertical, Shell Size 5, 2.77mm



TE Part # 5747193-2
50 RCPT RA/MS STD (SL)



TE Part # 5745116-2
50 RCPT RA/MS STD




TE Part # CAT-026-RAVSAP5277
D-Sub Receptacle Assembly: Vertical, Action Pin, Shell Size 5, 2.77mm



TE Part # 745116-2
50 RCPT RA/MS STD



TE Part # 747193-2
50 RCPT RA/MS STD (SL)



TE Part # 768340-1
UNIV HAND TOOL KIT AMPLATCH


Also in the Series | AMPLIMITE HDF



Connector Hardware(3)



Connector Strain Relief(5)



IDC D-Sub Connectors(36)

Customers Also Bought




TE Part #166679-1
MOD-4 PIN CONTACT



TE Part #60196-3
187 FASTON REC 20-16 AWG TPBR



TE Part #8-2176416-1
9W STD M/OX 5% 110K




TE Part #364100-E
DRCBTB 1,27 12 M BTB32 30,2 137 * 094 TR



TE Part #746785-1
50 POS STR RLF, LOW PROFILE




TE Part #2-1617146-9
JMGACDD-26M = M39016/19-036M



TE Part #284135-E
STVC 96 F ABC VW 7-00 EEUE 13,0 * 131 E



TE Part #4-1579008-8
EXTRACTION TOOL



Documents

Product Drawings

50 POS HDF PLUG, MS, LEAD FREE

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_1658607-1_A1.2d_dxf.zip

English

Customer View Model

ENG_CVM_1658607-1_A1.3d_igs.zip

English

Customer View Model

ENG_CVM_1658607-1_A1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

AMPLIMITE Subminiature D Connectors - Cable Connectors

English

AMPLIMITE Cable Connectors and Shielding Hardware Kits QRG

English

Product Specifications

Product Specification

English

Product Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

CSA Certificate



English