



## Datasheet for part number DAJK15P5-1A7N-146

|                                                                               |
|-------------------------------------------------------------------------------|
| Our Catalog Part Number: DAJK15P5-1A7N-146                                    |
| Our Global Manufacturing Part Number: 121560-0688                             |
| Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*JK / D*JT |

| Product Datasheet               |                                               |
|---------------------------------|-----------------------------------------------|
| General                         | Filter D                                      |
| Filter Type                     | tublar ceramic filter                         |
| Filter Capacity                 | 1500 pF                                       |
| Wire Gauge Range AWG            | AWG 20-28                                     |
| Mating Cycles                   | 200                                           |
| Dielectric Withstanding Voltage | 250 VAC at sea level                          |
| Current Rating Signal Contacts  | 5 A max.                                      |
| Contact Resistance              | 10 milli Ohm max                              |
| Operating Temperature           | -55°/+125°                                    |
| Salt Spray Test                 | 20 hours                                      |
| Shell Material                  | steel                                         |
| Shell Finish                    | tin                                           |
| Insulator Material              | glass filled Thermoplastic, type PCT UL 94V-0 |
| Insulator Color                 | white                                         |
| Number of Contacts              | 15 contacts size 20                           |
| Gender                          | Pin                                           |
| Contact Type                    | turned                                        |
| Contact Material                | copper alloy                                  |
| Contact Finish                  | gold flash (Performance Class 2)              |
| Contact Termination             | Right angled solder                           |
| Mounting Methode                | metal bracket and captive nut 4-40            |
| Row Spacing                     | 2,54 mm                                       |
| Pushfit Type                    | Pushfit for PCB hold diameter 3.0             |