





REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.06.27	阿树




SPECIFICATION
1.Rating : DC 30V 1.0A;
2.Contact resistance: $\leq 30\text{m}\Omega$
3.Insulation resistance: $\geq 100\text{M}\Omega$ (DC250V);
4.Withstand voltage: 500VAC ;
5.Insertion and extraction force: 5-30N;
6.life test: 5,000 cycles.



PJ-623A2 PCB LAYOUT



PJ-623A3 PCB LAYOUT



6	AXIS SUPPORT	1	BRASS	Ni-Plating
5	COVER	1	PBT	
4	3 CONTACT FOOT	1	BRONZE	CuSn-Plating
3	2 CONTACT FOOT	1	BRONZE	CuSn-Plating
2	1 CONTACT FOOT	1	BRONZE	CuSn-Plating
1	OUSING	1	PBT	
NO.	DESCRIPT	QTY	MATERIAL	PLATING

AuGLAR	$\pm 5^\circ$
X.	± 0.40
X.x	± 0.30
X.xx	± 0.20
X.xxx	± 0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树
CHECKED	
APPROVED	

VIEW:
UNIT: mm/in
SIZE: A4

MODEL TYPE: 6.5 PHONE JACK
PART NO.: PJ-623AX-X
DWG NO.: