

1		2		3		4		5		6		7		8							
SAMZO		REAC/ROHS								REV		ECN NO		DESRIPTION		DESIGN		APPROVAL		DATE	
										A1		NEW		Replace frame						2018.06.21	
E		■ 技术参数 SPECIFICATIONS																			
		◆ 适用线规: AWG.#28~#32 Applicable Wire: AWG.#28~#32																			
		◆ 额定电压: 50V DC/AC(rms) Rated voltage: 50V DC/AC(rms)																			
		◆ 额定电流: 1A (AWG.#28) Rated Current: 1A (AWG.#28)																			
		◆ 耐压值: 500V AC/minute Withstand voltage: 500V AC/min.																			
		◆ 工作温度: -25℃ ~ +85℃ Working Temp : -25℃ ~ +85℃																			
		◆ 绝缘电阻: ≥100 MΩ Insulation resistance: ≥100 MΩ																			
		◆ 接触电阻: ≤20 mΩ Contact resistance: ≤20 mΩ																			
D		■ 材料 MATERIAL																			
		◆ 绝缘体: 尼龙9T, UL94-V0 Insulator: PA9T, UL94-V0																			
		◆ 接触针: 磷铜 Contact PIN: Phosphor bronze																			
		◆ 焊片: 黄铜 Solder tab: Brass																			
C		A. SERISE: 6C-SHD																			
		B. SPACING: F-1.00mm																			
		C. MOUNTING: D-WT																			
		D. STANDARD: 2-Double Row																			
		E: PIN: 05-2P (05-25P)																			
		F: CODE: 0-REGULAR																			
		6C F D 2 ** 0																			
		A B C D E F																			