

Description

The SXG80N10NF uses advanced technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 10V. This device is suitable for use as a Battery protection or in other Switching application.

General Features

$V_{DS} = 100V$ $I_D = 80A$

$R_{DS(ON)} < 8m\Omega$ @ $V_{GS}=10V$



Application

DC/DC Converter

LED Backlighting

Power Management Switches

PDFN5*6-8L



Absolute Maximum Ratings ($T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	100	V
V_{GS}	Gate-Source Voltage	± 20	V
$I_D@T_A=25^\circ\text{C}$	Continuous Drain Current ¹	80	A
$I_D@T_A=70^\circ\text{C}$	Continuous Drain Current ¹	62	A
IDM	Pulsed Drain Current ²	240	A
EAS	Single Pulse Avalanche Energy ³	120	mJ
IAS	Avalanche Current	40	A
$P_D@T_A=25^\circ\text{C}$	Total Power Dissipation ⁴	135	W
TSTG	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$
$R_{\theta JA}$	Thermal Resistance Junction-Ambient ¹	62	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	0.84	$^\circ\text{C/W}$

Electrical Characteristics (T_c=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BVDSS	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =250uA	100	108	---	V
RDS(ON)	Static Drain-Source On-Resistance ²	V _{GS} =10V , I _D =13.5A	---	6.5	8.0	mΩ
	Static Drain-Source On-Resistance ²	V _{GS} =4.5V , I _D =11.5A	---	8.7	10.5	
VGS(th)	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	1.2	1.8	2.3	V
IDSS	Drain-Source Leakage Current	V _{DS} =80V , V _{GS} =0V , T _J =25°C	---	---	1	uA
		V _{DS} =80V , V _{GS} =0V , T _J =55°C	---	---	5	
IGSS	Gate-Source Leakage Current	V _{GS} =±20V , V _{DS} =0V	---	---	±100	nA
gfs	Forward Transconductance	V _{DS} =5V , I _D =13.5A	---	75	---	S
Qg	Total Gate Charge (10V)	V _{DS} =50V , V _{GS} =10V , I _D =13.5A	---	45	---	nC
Qg	Total Gate Charge (4.5V)		---	19.3	---	
Qgs	Gate-Source Charge		---	9.5	---	
Qgd	Gate-Drain Charge		---	4.8	---	
Td(on)	Turn-On Delay Time	V _{DD} =50V , V _{GS} =10V , R _G =3Ω, I _D =13.5A	---	10	---	ns
Tr	Rise Time		---	6.5	---	
Td(off)	Turn-Off Delay Time		---	45	---	
Tf	Fall Time		---	7.5	---	
Ciss	Input Capacitance	V _{DS} =50V , V _{GS} =0V , f=1MHz	---	3320	---	pF
Coss	Output Capacitance		---	605	---	
Crss	Reverse Transfer Capacitance		---	20	---	
IS	Continuous Source Current ^{1,5}	V _G =V _D =0V , Force Current	---	---	5	A
VSD	Diode Forward Voltage ²	V _{GS} =0V , I _S =1A , T _J =25°C	---	---	1.1	V
trr	Reverse Recovery Time	I _F =13.5A , di/dt=100A/μs , T _J =25°C	---	33	---	nS
Q _{rr}	Reverse Recovery Charge		---	150	---	nC

Note :

- 1、The data tested by surface mounted on a 1 inch 2 FR-4 board with 2OZ copper.
- 2、The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%
- 3、The EAS data shows Max. rating . The test condition is V_{DD}=72V,V_{GS}=10V, L=0.1mH I_{AS}=40
- 4、The power dissipation is limited by 150°C junction temperature
- 5、The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation

Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs. G-S Voltage




Fig.3 Source-Drain Forward Characteristics




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs. T_J




Fig.6 Normalized $R_{DS(on)}$ vs. T_J

Typical Characteristics




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform





Fig.11 Unclamped Inductive Switching Waveform

Package Mechanical Data-PDFN5*6-8L-JQ Single


Symbol	Common			
	mm		Inch	
	Mim	Max	Min	Max
A	1.03	1.17	0.0406	0.0461
b	0.34	0.48	0.0134	0.0189
c	0.824	0.0970	0.0324	0.082
D	4.80	5.40	0.1890	0.2126
D1	4.11	4.31	0.1618	0.1697
D2	4.80	5.00	0.1890	0.1969
E	5.95	6.15	0.2343	0.2421
E1	5.65	5.85	0.2224	0.2303
E2	1.60	/	0.0630	/
e	1.27 BSC		0.05 BSC	
L	0.05	0.25	0.0020	0.0098
L1	0.38	0.50	0.0150	0.0197
L2	0.38	0.50	0.0150	0.0197
H	3.30	3.50	0.1299	0.1378
I	/	0.18	/	0.0070

Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
TAPING	PDFN5*6-8L		5000