

Actuator

31-
718.0292

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/31-718.0292>

Your product:



31-718.0292

Actuator

FRONT

Front dimension:	18 mm x 18 mm
Front bezel material:	Plastic
Front bezel colour:	Black
Front form:	square

MOUNTING

Design:	raised
Mounting cut-out:	Ø 16 mm

OPERATING-/INDICATION PART

Lens illumination:	illuminative
--------------------	--------------

ELECTRICAL CHARACTERISTICS

Protection class:	II
Electrical lifetime:	50 000 cycles of operation
Electric strength:	2500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth
Switching voltage and switching current:	250 VAC, 5 A (ohmic) 250 VAC, 3 A (Soldering terminal) 250 VAC, 2 A (inductive, $\cos(\phi) = 0.7$) 125 VAC, 3 A (inductive, $\cos(\phi) = 0.7$) 220 VDC, 0.1 A (inductive, L:R = 30 ms) 60 VDC, 0.7 A (inductive, L:R = 30 ms) 24 VDC, 2 A (inductive, L:R = 30 ms)
Standards:	According to EN/IEC 61058-1
Contacts:	1 NC / 1 NO

Thermal current I_{th}:	5 A
Rated Operational Voltage U_e:	250 VAC/VDC

MECHANICAL CHARACTERISTIC

Mechanical lifetime:	1 Mio. cycles of operation
Weight:	0.008 kg
Switching system:	Self-cleaning, double-break snap action switching system (contact opening width 2 mm x 0.5 mm), 1 normally closed and 1 normally open contact per element.
Contact material:	Gold
Switching action:	Maintained
Terminal:	Universal soldering terminal
Tightening torque:	Fixing nut max. 0.5 Nm
Operating force:	2 N ... 5,5 N, depending on the number of switching elements
Switching system:	Snap-action switching element
Operating Travel:	ca. 3 mm

AMBIENT CONDITION

IP Protection:	IP40 front side, IP67 with front protective cap
Climate resistance:	Standard condition according to IEC 60068-2-3 Changing condition according to IEC 60068-2-14
Storage temperature:	– 40 °C ... + 85 °C
Shock resistance:	15 g for 11 ms, as per IEC 60512-4-3, IEC 60068-2-27 (Single impacts, semi-sinusoidal)
Vibration resistance:	10 g at 10 Hz...2000 Hz, amplitude 1.5 mm (Sinusoidal), according to DIN EN 60512-4-4, DIN EN 60068-2-6
Operating temperature:	– 25 °C ... + 55 °C, mounted as a block, make sure the heat can escape freely

CERTIFICATE

Approbations:	CB (IEC 61058-1), CSA, DNV, ENEC (EN 61058-1), UL
Conformities:	CE, UKCA, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

OTHER

max. number of switching elements:	1
Internal size:	

15,3 mm x 15,3 mm


Housing colour:

Black

Short Description:

Actuator, Ø 16 mm, 18 mm x 18 mm, illuminative, square, Black, Plastic, 1 NC / 1 NO, Maintained, Universal soldering terminal

Dimension drawings:




A = Solder terminal

B = Plug-in terminal 2.8 mm x 0.5 mm

C = Universal terminal 2.0 mm x 0.5 mm

D = Universal-Solder terminal

Component layouts:




A = Terminals (rear side)

B = Diode block

C = Anti twist device only 18 mm x 24 mm

D = Drilling plan (component side)

Mounting cut-outs:



Wiring diagrams:

