


REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1	-	RELEASE DRAWING	04JAN21	SULLEN	TOMMY
A2	-	UPDATE DRAWING	10MAY21	SULLEN	TOMMY




PART NUMBER CHART				
PART NUMBER	SEAL	HOUSING COLOR	STRAIN RELIEF COLOR	WEIGHT (GRAMS)
ATP06-6S-SR01	STANDARD	GREY	BLACK	20.5
ATP06-6S-SR01BK	STANDARD	BLACK	BLACK	20.5
ATP06-6S-SR02	REDUCED DIA.	GREY	BLACK	20.5
ATP06-6S-SR02BK	REDUCED DIA.	BLACK	BLACK	20.5

ATP06-6S-SR0X		DESCRIPTION		ITEM
QUANTITY	PART NUMBER	MATERIALS LIST		
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric (mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 3) Note reference =		SIGNATURES	DATE	
		DRAWN: SULLEN, ZHANG	10MAY21	
		CHECKED: ORION, LI	11MAY21	
		ENGINEER:		
		APPROVAL: TOMMY, XIE	12MAY21	
		CUSTOMER:		
PROCESS SPECIFICATIONS:		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		
NEXT ASSY:		SIZE B	TYPE C-	DWG NO. ATP06-6S-SR0X
		SCALE: NONE		REVISION A2
		SHEET 1 OF 1		

Amphenol
Sine Systems - www.amphenol-sine.com
44724 Morley Drive
Clinton Township, MI 48036

6 POS, PLUG, SOCKET, ATP SERIES,
STRAIN RELIEF END CAP



REQUIRES CONTACT RETENTION WEDGE AWP-6S

STRAIN RELIEF END CAP - BLACK - ALL CONNECTORS

CONNECTOR STANDARD COLOR IS GREY. OTHER COLORS FOR OPTION.

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

23.9

28.1

48.5±0.6

6

ATP06-6S

A Series™ - Contact Size 12 Options (Works with: AHD-6, ATP, ATHD, DuraMate and PanelMate Series)

Machined Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Type
*AT60-204-12141-10	Male Contact - Pin, Nickel-plated	12	10-12	Machined
*AT62-203-12141-10	Female Contact - Socket, Nickel-plated	12	10-12	Machined
AT60-220-1231	Male Contact - Pin, Gold-plated	12	12-14	Machined
AT62-210-1231	Female Contact - Socket, Gold-plated	12	12-14	Machined
AT60-204-12141	Male Contact - Pin, Nickel-plated	12	12-14	Machined
AT62-203-12141	Female Contact - Socket, Nickel-plated	12	12-14	Machined

*Works with ATP Series only

DiagnosticGrade™ Machined Contacts, Sockets & Pins				
• Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective				
Part Number	Description	Size	AWG	Type
65-54749	Male Contact - DiagnosticGrade™, Pin, Gold-plated	12	20	Machined
AT62-210-1231-1820	Female Contact - DiagnosticGrade™, Socket, Gold-plated	12	20	Machined

Tooling - Machined Contacts	
Part Number	Description
AUTK-12	Hand Crimp Tool, Size 12
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20
M300-25A	Hand Crimp Tool used with Crimp Locator MFX-3966, Size 12, 10AWG
MFX-3966	Contact Locator used with Hand Crimp Tool M300-25A, Size 12, 10AWG

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)	
Part Number	Description
ATRT-100	Contact and Wedgelock Extraction Tool
AT11-337-1205	Contact Removal Tool, Plastic, Size 12

Sealing Plugs (For both Machined or Stamped & Formed Contacts)	
Part Number	Description
A114017	Sealing Plug, Size 12, White

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Type
AT60-12-0244	Male Contact - Pin, Gold-plated	12	10-12	Stamped & Formed
AT62-12-0244	Female Contact - Socket, Gold-plated	12	10-12	Stamped & Formed
AT60-12-0222	Male Contact - Pin, Nickel-plated	12	10-12	Stamped & Formed
AT62-12-0222	Female Contact - Socket, Nickel-plated	12	10-12	Stamped & Formed
AT60-12-0144	Male Contact - Pin, Gold-plated	12	12-14	Stamped & Formed
AT62-12-0144	Female Contact - Socket, Gold-plated	12	12-14	Stamped & Formed
AT60-12-0166	Male Contact - Pin, Nickel-plated	12	12-14	Stamped & Formed
AT62-12-0166	Female Contact - Socket, Nickel-plated	12	12-14	Stamped & Formed

Tooling - Stamped & Formed Contacts	
Part Number	Description
MFX-3973	Crimp Die - Size 12
MFX-3985	Crimp Die - Ssize 12, 10-12AWG -02XX Series
ATT-12-00	Hand Crimp Tool - Size 12, 12AWG
ATT-12-01	Hand Crimp Tool - Size 12, 10AWG