



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Insulation Boots & Sleeves



Insulation Boot & Sleeve Product Type: **Insulation Boot**

Primary Product Material: **PVC**

Primary Product Color: **Black**

Packaging Method: **Bag**

Operating Temperature Range: **-40 – 105 °C [-40 – 221 °F]**

Features

Product Type Features

| | |
|---------------------------------------|-----------------|
| Insulation Boot & Sleeve Product Type | Insulation Boot |
|---------------------------------------|-----------------|

Body Features

| | |
|--------------------------|-------|
| Primary Product Material | PVC |
| Primary Product Color | Black |

Dimensions

| | |
|----------------|-------------------|
| Product Length | 47.7 mm[1.878 in] |
|----------------|-------------------|

Usage Conditions

| | |
|-----------------------------|----------------------------|
| Operating Temperature Range | -40 – 105 °C[-40 – 221 °F] |
|-----------------------------|----------------------------|

Industry Standards

| | |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|

Packaging Features

| | |
|--------------------|-----|
| Packaging Quantity | 100 |
| Packaging Method | Bag |



Product Compliance

For compliance documentation, visit the product page on TE.com>

| | |
|---|--|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: MCCP (5% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Customers Also Bought



TE Part #413985-1
PLUG ASSY,STR,SMB



TE Part #6648239-1
JUMPER,CRN SKT



TE Part #58641-1
PRO-CRIMP TL & DIE MOD IV



TE Part #6648234-1
CONTACT,SKT,#0



TE Part #6-2213766-1
AV19 DPL 3A POWER LED WHITE 12V

TE Part #1-1879074-7
THS15 12R 5%

TE Part #ASHD622-24320PN016
PLUG ASSY.ASHD. 24320 PLANFORM.
16MM CRI

TE Part #6-1532166-6
094-4105-9003=MCK-N1-X1-9PRT1

TE Part #6-1532166-7
094-4706-9003=MCK-N1-X1-51SRT1

Documents

CAD Files

Customer View Model
ENG_CVM_CVM_1651003-1_C.2d_dxf.zip
English

3D PDF
3D

Customer View Model
ENG_CVM_CVM_1651003-1_C.3d_igs.zip
English
Customer View Model
ENG_CVM_CVM_1651003-1_C.3d_stp.zip
English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

POWER_CONNECTORS_CATALOG_SEC02_CABLE_MOUNTED
English
Busbar Power Brochure
English

Product Specifications

Application Specification
English

Agency Approvals

Agency Approval Document
English

1651003-1

901-0121-32031=BOOT,INSULATING

