



**Part Number :** [1300910013](#)  
**Product Description :** Woodhead Standard  
Duty Reel with Flying Leads, 16/3 SJTOW Cord,  
15.24m (50.0') Cord Length  
**Series Number :** 130091  
**Status :** Active  
**Product Category :** Electrical Reels  
**Engineering Number :** 980



---

## Documents & Resources

**Drawings**  
[Drawing 1300910013\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |                                                   |
|--------------------|---------------------------------------------------|
| GADSL/IMDS         | Not Relevant                                      |
| China RoHS         | Not Reviewed per SJ/T 11365-2006                  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21                   |
| REACH SVHC         | Not Reviewed per D(2024)4144-DC<br>(27 June 2024) |
| EU RoHS            | Not Reviewed per EU 2015/863                      |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

|                    |                                                                                            |
|--------------------|--------------------------------------------------------------------------------------------|
| Status             | Active                                                                                     |
| Category           | Electrical Reels                                                                           |
| Series             | 130091                                                                                     |
| Description        | Woodhead Standard Duty Reel with Flying Leads, 16/3 SJTOW Cord, 15.24m (50.0') Cord Length |
| Enclosure Rating   | NEMA 1                                                                                     |
| NEMA Configuration | NEMA 5-15                                                                                  |
| Product Family     | Reels - Woodhead                                                                           |
| Product Name       | Super-Safeway                                                                              |
| Type               | Cord Reel                                                                                  |
| UPC                | 78678833606                                                                                |

### Agency

|     |         |
|-----|---------|
| CSA | LR29921 |
| UL  | E22769  |

### Electrical

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 8.0A |
| GFCI                          | No   |
| Lamp Wattage - Maximum        | N/A  |
| On/Off Switch                 | N/A  |
| Voltage - Maximum             | 120V |

### Physical

|                |                |
|----------------|----------------|
| Bulb Included  | N/A            |
| Cable Length   | 0.457m (1.50') |
| Cable Movement | Ratchet Lock   |
| Cord Length    | 15.24m (50.0') |
| Cord Type      | 16/3 SJTOW     |
| Depth          | 0.30m (11.75") |

|                          |                     |
|--------------------------|---------------------|
| Drum Lock                | Ratchet             |
| Duty                     | Standard            |
| Guide Arm                | 2 - Position        |
| Height                   | 0.36m (14.25")      |
| Lamp Type                | N/A                 |
| Material - Coating       | Powder Coating      |
| Material - Housing       | Steel/Polycarbonate |
| Mounting Style           | Rigid               |
| Net Weight               | 8.518/kg            |
| Number of Conductors     | 3                   |
| Packaging Type           | Carton              |
| Primary Cord/Cable Entry | N/A                 |
| Retraction Weight        | 1.4kg (3.0 lb)      |
| Width                    | 196.85mm (7.750")   |
| Wire Size (AWG)          | 16                  |