



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Locking Lance Height	1.4 mm[.055 in]
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Terminal Material Thickness	.4 mm[.015 in]
Product Length	29.18 mm[1.149 in]
Compatible Insulation Diameter Range	3.1 – 4.1 mm[.12 – .16 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 720725-1 DAHT 250 FASTIN-ON TAB REC 18-14 ASSY	 TE Part # 1-1579007-4 EXTRACTION TOOL	 TE Part # 4-1579007-3 EXTRACTION TOOL KIT	 TE Part # 58524-1 PROCRIMPER TOOL & DIE
 TE Part # 641256-1 BLADE TAB 250 18-14AWG BR LP	 TE Part # 154660-2 FASTON 250 TAB 22-18 AWG TPBR	 TE Part # 58524-2 PROCRIMPER DIE	 TE Part # 880654-1 .250 SERIES FASTIN-

Also in the Series | FASTIN-FASTON 250

 Crimp Terminal Housings(210)	 Insertion & Extraction Tools(2)	 PCB Terminals(2)	 Quick Disconnects(251)
---	---	---	---

Customers Also Bought



TE Part #1-1622825-8 RL73K 3A R27 5% 1K RL	TE Part #1-480424-9 04P CMNL PLUG HSG F/H BLK	TE Part #2-2106003-2 Connector, SMT-IDC, 2 position, 22AWG	TE Part #3-2176327-5 CRGP 0805 6K8 1%
TE Part #1-967626-2 TAB HOUSING, 2,8MM 9POS	TE Part #DT04-2P-P004 REC, 2P, GRY, N	TE Part #6-1415073-1 RT3S4T30	TE Part #1-480303-9 03P CMNL PLUG HSG F/H BLK

Documents

Product Drawings

FF 250 TAB 18-16AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42241-1_AB.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_42241-1_AB.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42241-1_AB.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

FASTIN-FASTON CONN. .110 INCH, .187 INCH, .250 INCH, .375 INCH SRS.

English

Product Specification

English



Instruction Sheets

Instruction Sheet (non U.S.)

Japanese

Instruction Sheet (non U.S.)

Japanese