

Specifications:
规格:
Voltage rating: 150V AC/DC
额定电压: 150V AC/DC
Current rating: 0.5A AC/DC
额定电流: 0.5A AC/DC
Withstanding voltage: 150V AC/minute
耐受电压: 150V AC/分钟
Temperature range: -40℃ ~ +85℃
温度范围: -40℃ ~ +85℃
Insulation resistance: 100MΩ min
绝缘电阻: 100MΩ Min
Contact resistance: 50mΩ Max
接触电阻: 50mΩ Max




X0502	F	V	S-XX	E	S-LP	SN
(1)	(2)	(3)	(4)	(5)	(6)	(7) (8) (9)

- 1.Series No
- 2.Category:F-Female
- 3.Welding Board Angle:V-Stright 180°
- 4.Welding Way:S-SMT
- 5.Row No.Pin No:XX-10~80P
- 6.Height: E:2.8mm
- 7.Special No:S-With positioning column
- 8.Material:LP-LCP UL94V-0
- 9.Plating:SN-Tin Plated

Poles	Dimensions(mm)				Poles	Dimensions(mm)			
	A	B	C	D		A	B	C	D
10	4.70	2.00	3.20	4.10	32	10.20	7.50	8.70	9.60
12	5.20	2.50	3.70	4.60	36	11.20	8.50	9.70	10.60
14	5.70	3.00	4.20	5.10	40	12.20	9.50	10.70	11.60
20	7.20	4.50	5.70	6.60	50	14.70	12.00	13.20	14.60
22	7.70	5.00	6.20	7.10	60	17.20	14.50	15.70	16.60
24	8.20	5.50	6.70	7.60	80	22.20	19.50	20.70	21.60
30	9.70	7.00	8.20	9.10	/				

X0502FVS-XXES-LPSN	LCP	Copper Alloy	X0502W	3.5mm
PART NO	Material	Material(Pin)	Suitable XKB Wafer	Mating height

							DSND		SCALE: N/A	MODEL TYPE: 0.5mm BTB Connector		
Δx					ANGLAR	±5°		DWN		VIEW: 	PART NO.: X0502FVS-XXES-LPSN	
Δx					4<L≤ 16	±0.3		CHKD		UNIT: mm/in	DWG NO.: X-X0502FVS-XXES-LPSN	
Δx					16<L≤ 63	±0.4		APPD		SIZE: A4		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	L> 63	±0.5						
REVISIONS							UNSPECIFIED TOLERANCES			WEIGHT		
www.helloxkb.com www.helloxkb.cn www.xk-da.cn							XKB INDUSTRIAL PRECISION CO.,LIMITED			SHEET		
										1/1		
										REVISION		
										A0		