

FL MGUARD 1102 - Router

1153079

<https://www.phoenixcontact.com/us/products/1153079>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Industrial NAT firewall, comprehensive NAT functionality, intelligent stateful inspection firewall, protection without configuration in Easy Protect Mode, Firewall Assistant as a simple configuration wizard, non-blocking validation of the configuration in test mode

Product description

NAT firewall

Your advantages

- The new Firewall Assistant helps you to create Firewall rules
- High data throughput
- Inexpensive entry into network security
- Test Mode: easily test the created firewall rules without limiting system availability
- Easy Protect Mode: without requiring any configuration, wire bridges are used to block external network access attempts

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1153079 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | DN27 |
| Product key | DNN311 |
| GTIN | 4063151152413 |
| Weight per piece (including packing) | 413.28 g |
| Weight per piece (excluding packing) | 310.07 g |
| Customs tariff number | 85176200 |
| Country of origin | DE |

FL MGUARD 1102 - Router

1153079

<https://www.phoenixcontact.com/us/products/1153079>



Technical data

Dimensions

| | |
|--------|----------|
| Width | 45 mm |
| Height | 130 mm |
| Depth | 133.8 mm |

Notes

Note on application

| | |
|---------------------|-------------------------|
| Note on application | Only for industrial use |
|---------------------|-------------------------|

Material specifications

| | |
|------------------|--------------------------------|
| Color | gray |
| Housing material | Polycarbonate fiber reinforced |

Interfaces

Ethernet

| | |
|----------------------|--|
| Connection method | RJ45 |
| Transmission speed | 10/100/1000 Mbps |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission length | 100 m (per segment) |
| Signal LEDs | Supply voltage, data transmission, error, link, activity |
| No. of channels | 2 (RJ45 ports) |

Signal contact

| | |
|-------------------|---------------------------------|
| Connection method | Push-in-/Spring-cage connection |
| Additional text | not electrically isolated |

System properties

Functionality

| | |
|-----------------|---|
| Basic functions | NAT firewall with intelligent firewall, slot for SD memory card |
|-----------------|---|

System requirements

| | |
|--------------------|---|
| Supported browsers | Firefox, Chrome, Edge in the latest version |
|--------------------|---|

Product properties

| | |
|--------------------|----------------------------------|
| Product type | Security router for the DIN rail |
| Product family | Security-Router |
| Type | Stand-Alone |
| Special properties | NAT |

Data management status

| | |
|------------------|----|
| Article revision | 08 |
|------------------|----|

FL MGUARD 1102 - Router

1153079

<https://www.phoenixcontact.com/us/products/1153079>



Insulation characteristics

| | |
|------------------|---------------------------------------|
| Protection class | III (IEC 61140, EN 61140, VDE 0140-1) |
|------------------|---------------------------------------|

Security functions

| | |
|------------------------------------|---|
| Filtering | IP, port, protocol |
| Firewall rules | Stateful inspection firewall |
| Basic functions | NAT firewall with intelligent firewall, slot for SD memory card |
| Network Time Protocol (NTP) client | Client/server |
| Routing | Standard routing, NAT, 1:1-NAT, port forwarding |
| Protection against | IP spoofing, DoS and Syn Flood Protection |

Electrical properties

| | |
|---|--|
| Local diagnostics | US1 Supply voltage US1 Green LED |
| | One LED per port Link active Green LED |
| Maximum power dissipation for nominal condition | typ. 2.88 W |

Supply

| | |
|-----------------------------|--|
| Supply voltage (DC) | 24 V DC |
| Supply voltage range | 18 V DC ... 32 V DC |
| Power supply connection | via COMBICON, max. conductor cross section 1.5 mm ² |
| Residual ripple | 3.6 V _{PP} (within the permitted voltage range) |
| Max. current consumption | 1000 mA (loaded outputs) |
| Typical current consumption | 120 mA (at 24 V DC) |

Function

| | |
|--------------------------------|------------------------------|
| Signal contact control voltage | 24 V DC (typical) |
| Signal contact control current | 250 mA (short-circuit-proof) |

Environmental and real-life conditions

Ambient conditions

| | |
|---|-------------------------------|
| Degree of protection | IP20 |
| Ambient temperature (operation) | 0 °C ... 60 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |

Approvals

Conformity/Approvals

| | |
|-------------|--------------|
| Conformance | CE-compliant |
|-------------|--------------|

Mounting

| | |
|---------------|-------------------|
| Mounting type | DIN rail mounting |
|---------------|-------------------|

EMC data

| | |
|---------------------------------|--|
| Conformance with EMC directives | IEC 61000-6-2 IEC 61000-4-2 (ESD) 6 kV contact discharge, 8 kV air discharge |
|---------------------------------|--|

FL MGUARD 1102 - Router



1153079

<https://www.phoenixcontact.com/us/products/1153079>

| | |
|-------------------------------|--|
| | IEC 61000-6-2 IEC 61000-4-3 (immunity to radiated interference) 10 V/m (80 MHz ... 2000 MHz) |
| | IEC 61000-6-2 IEC 61000-4-4 (burst) 2 kV power line, 1kV data line |
| | IEC 61000-6-2 IEC 61000-4-5 (surge) power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line |
| | IEC 61000-6-2 IEC 61000-4-6 (immunity to conducted interference) 3 V (10 kHz ... 150 kHz), 10 V (150 kHz ... 80 MHz) |
| Noise immunity | EN 61000-6-2:2005 |
| Electromagnetic compatibility | Conformance with EMC Directive 2014/30/EU |
| Noise emission | EN 55022 / Class B |

Signaling

| | |
|----------------|--|
| Status display | Supply voltage, data transmission, error, link, activity |
|----------------|--|

FL MGUARD 1102 - Router

1153079

<https://www.phoenixcontact.com/us/products/1153079>



Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1153079>



cUL Listed

Approval ID: E238705



cULus Listed

Approval ID: E366272

FL MGUARD 1102 - Router

1153079

<https://www.phoenixcontact.com/us/products/1153079>



Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 19170406 |
| ECLASS-12.0 | 19170406 |
| ECLASS-13.0 | 19170406 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001478 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 43222600 |
|-------------|----------|

Environmental product compliance

| | |
|---|---|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(a), 7(c)-I |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | 4,4'-isopropylidenediphenol(CAS: 80-05-7) |
| | Lead(CAS: 7439-92-1) |
| SCIP | ddb18c11-cdf6-436d-acb6-49cf41b969bf |

FL MGUARD 1102 - Router

1153079

<https://www.phoenixcontact.com/us/products/1153079>



Accessories

FL MGUARD DM UNLIMITED - Software

2981974

<https://www.phoenixcontact.com/us/products/2981974>



Central device management software for MGUARD devices for any number of devices in the field. For installation on a PC. No additional licenses required. Download trial version for up to 10 devices.

MGUARD SECURE VPN CLIENT LIC - License

2702579

<https://www.phoenixcontact.com/us/products/2702579>



License for mGuard Secure VPN Client v11.x

FL MGUARD 1102 - Router

1153079

<https://www.phoenixcontact.com/us/products/1153079>



SD FLASH 2GB - Program/configuration memory

2988162

<https://www.phoenixcontact.com/us/products/2988162>



Program and configuration memory, for extending the internal flash memory, pluggable, 2 GB.

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com