



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.34 – .75 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.25 mm[.01 in]
Product Length	16.1 mm[.634 in]
Compatible Insulation Diameter Range	1.5 – 2.5 mm[.059 – .098 in]
Wire Size	.34 – .75 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	12000
Packaging Method	Strip/Reel

Other

Line	Premier
------	---------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 141939-1
110 FASTON, FLAG, REC., 22-18 AWG, BR

TE Part # 2150049-1
OCEAN-2.0-APPLICATOR-E-062F090F-REM

TE Part # 2150049-2
OCEAN-2.0-APPLICATOR-E-062F090FA-REA

TE Part # 2150636-1
OCEAN-2.0-APPLICATOR-S-062F090OV-RSM

TE Part # 2150636-2
OCEAN-2.0-APPLICATOR-S-062F090OVA-RSA

TE Part # 7-2150049-7
OCEAN_2.0_SPARE_PART_KIT-062F090F

TE Part # 7-2150636-7
OCEAN_2.0_SPARE_PART_KIT-062F090OV

Also in the Series | FASTON 110

Crimp Terminal Housings(13)


Insertion & Extraction Tools(1)

PCB Terminals(22)

Quick Disconnects(168)

Customers Also Bought



 TE Part #206903-2 SEALING CAP ASSY,SZ 11,CPC	 TE Part #2040008-1 INDUSTRIAL MINI I/O PLUG KIT D2	 TE Part #321280 SPLICE,SOLIS BUTT 14-12	 TE Part #2-66105-0 III+ SKT,24-20,TIN,SMPACK
 TE Part #1-967239-1 Timer Connector Housing	 TE Part #1393364-1 V23540X7000Y10=GET-FEM TERM AU	 TE Part #7-1452656-1 MCON 1.2 LL REC SRC SN	 TE Part #2-515230-2 SPRING PLATE, LINEAR FEEDER MC

Documents

Product Drawings

110 FASTON,REC.,22-18 AWG,PTBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_140825-2_AS.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_140825-2_AS.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_140825-2_AS.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Wire Preparation And Crimp Inspection Guide

English

Agency Approvals

Agency Approval Document

English