

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Standard extruded heatsinks](#) » [SK 04 ...](#) » **SK 04**



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
 - [Standard extruded heatsinks](#)
 - Extruded heatsinks for lock-in retaining spring
 - Extruded heatsinks for PCB mounting
 - Extruded heatsinks for DC/DC converter
 - Retaining springs for transistors
 - U-Extruded heatsinks
 - Die-cast heatsinks
 - Fin coolers
 - Fluid coolers
 - Aluminium flat-, quadrangular-, angled-, U- & T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Board Level heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components
- ▶ **Cases f.case**
- ▶ **Connectors f.con**

Standard extruded heatsinks

SK 04 ...

SK 04 1000 SA

97 x 25 mm, with guideway for cover plates or blanks

add to request



Features

Technical Drawing

Service

width	97 mm
height	25 mm
plate thickness	4 mm
length	1000 mm
thermal resistance R_{θ}	2.8 - 1.3 K/W
drilling pattern	TO 3
	CB
	SSR 1
	SSR 2
surface	black anodised