

- Find by Feature
- Browse by Category
- Browse by Application
- Share

Clips, Clamps

Data Connectors

Header Systems

Liquid Silicone Technology

Other Connectors

Safety Relays

Standard Automotive Connections

Terminal Strippers

Suppliers

Enter part number or keyword

- Search Results (0)
- Search Options

No Search Results

Select a product type to narrow your search:

Results with your selections: --

Blade size [mm]

- ☐ 0.50
- ☐ 0.64
- ☐ 0.8
- ☐ 1.0
- ☐ 1.0 (round)
- ☐ 1.2
- ☐ 1.5
- ☐ 1.6 (round)
- ☐ 1.8
- ☐ 2.0 (round)
- ☐ 2.3
- ☐ 2.4 (round)
- ☐ 2.8
- ☐ 3.3
- ☐ 3.4
- ☐ 3.9
- ☐ 4.1
- ☐ 4.8
- ☐ 5.7
- ☐ 6.3
- ☐ 7.0
- ☐ 7.6
- ☐ 8.0
- ☐ 9.5
- ☐ 10.0
- ☐ 20.0

Terminal family

- ☐ 56
- ☐ 59
- ☐ 090
- ☐ ATS
- ☐ Apex
- ☐ Auto Fuse
- ☐ BFC
- ☐ BTS
- ☐ Battery
- ☐ Bus Circuit
- ☐ CTS
- ☐ DCK
- ☐ DCS
- ☐ DS
- ☐ DSQ
- ☐ Ducon
- ☐ DuoTwin
- ☐ Ferrule
- ☐ Flexible Power
- ☐ Fuse
- ☐ GT
- ☐ GT Flex Beam
- ☐ GTS
- ☐ HES
- ☐ HPCS

- ☐ HVF
- ☐ HVF II
- ☐ Heavy Duty
- ☐ Hylok
- ☐ IDC
- ☐ Ignition
- ☐ Lamp Socket
- ☐ MCS
- ☐ MTS
- ☐ MTS-B
- ☐ Metri-Pack
- ☐ Micro 64
- ☐ Micro HVT
- ☐ Micro-Pack
- ☐ OCS
- ☐ Pack-Con
- ☐ Performance Pack
- ☐ Power Pack
- ☐ RCS
- ☐ Ring
- ☐ Sicma
- ☐ Spade
- ☐ Splice
- ☐ TTS
- ☐ USB MINI-B
- ☐ VF
- ☐ Weather Pack



Search → Clear

#### Plating

- ☐ Bronze
- ☐ Chrome
- ☐ Gold
- ☐ Gold + Nickel
- ☐ Gold + Tin
- ☐ Nickel
- ☐ Nickel + Tin
- ☐ Palladium
- ☐ Palladium / Gold
- ☐ Palladium-Gold-Nickel
- ☐ Silver
- ☐ Silver + Tin
- ☐ Tin
- ☐ Tin over Copper
- ☐ Tin, Lead
- ☐ Unplated



Search → Clear

#### Gender

- ☐ Female
- ☐ Male
- ☐ Male + Female
- ☐ Male + Male
- ☐ Splice



Search → Clear

#### Sealed

- ☐ Mat Sealed
- ☐ Sealed
- ☐ Unsealed



Search → Clear

Inside Ring Diameter [mm]



- ☐ 0.20
- ☐ 0.28
- ☐ 0.35
- ☐ 3.20
- ☐ 3.60
- ☐ 3.73
- ☐ 3.74
- ☐ 4.21
- ☐ 4.30
- ☐ 4.39
- ☐ 5.13
- ☐ 5.18
- ☐ 5.30
- ☐ 5.40
- ☐ 5.53
- ☐ 5.60
- ☐ 6.00
- ☐ 6.10
- ☐ 6.20
- ☐ 6.33
- ☐ 6.40
- ☐ 6.50
- ☐ 6.60
- ☐ 6.70
- ☐ 6.87
- ☐ 7.10
- ☐ 7.11
- ☐ 7.15
- ☐ 7.16
- ☐ 7.21
- ☐ 8.30
- ☐ 8.40
- ☐ 8.50
- ☐ 8.71
- ☐ 8.76
- ☐ 8.80
- ☐ 9.50
- ☐ 9.52
- ☐ 9.90
- ☐ 10.00
- ☐ 10.26
- ☐ 10.29
- ☐ 10.32
- ☐ 10.33
- ☐ 10.34
- ☐ 10.40
- ☐ 10.50
- ☐ 10.60
- ☐ 11.96
- ☐ 12.00
- ☐ 12.70
- ☐ 12.80
- ☐ 12.85
- ☐ 12.90
- ☐ 13.00
- ☐ 13.53
- ☐ 13.54



.

Search →

Clear

Outside Ring Diameter [mm]



- ☐ 0.47
- ☐ 0.62
- ☐ 0.81
- ☐ 6.35
- ☐ 7.92
- ☐ 8.00
- ☐ 8.70
- ☐ 8.73
- ☐ 8.74
- ☐ 8.75
- ☐ 8.80
- ☐ 9.00
- ☐ 9.53
- ☐ 10.00
- ☐ 10.34
- ☐ 10.40
- ☐ 10.92

- ☐ 11.30
- ☐ 11.50
- ☐ 11.56
- ☐ 11.58
- ☐ 11.80
- ☐ 12.00
- ☐ 13.00
- ☐ 14.27
- ☐ 14.28
- ☐ 14.40
- ☐ 14.45
- ☐ 14.98
- ☐ 15.00
- ☐ 15.20
- ☐ 15.74
- ☐ 15.84
- ☐ 17.40
- ☐ 17.45
- ☐ 17.48
- ☐ 18.00
- ☐ 19.00
- ☐ 19.05
- ☐ 20.00
- ☐ 20.60
- ☐ 20.62
- ☐ 22.35
- ☐ 22.40
- ☐ 23.00
- ☐ 28.56
- ☐ 28.60



•

Search → Clear

Minimum Cable Core Cross Section [mm2]



- ☐ 0.01
- ☐ 0.08
- ☐ 0.13
- ☐ 0.14
- ☐ 0.20
- ☐ 0.22
- ☐ 0.25
- ☐ 0.30
- ☐ 0.33
- ☐ 0.35
- ☐ 0.40
- ☐ 0.50
- ☐ 0.52
- ☐ 0.55
- ☐ 0.60
- ☐ 0.70
- ☐ 0.75
- ☐ 0.80
- ☐ 0.82
- ☐ 0.85
- ☐ 1.00
- ☐ 1.10
- ☐ 1.20
- ☐ 1.25
- ☐ 1.30
- ☐ 1.31
- ☐ 1.35
- ☐ 1.40
- ☐ 1.50
- ☐ 1.60
- ☐ 2.00
- ☐ 2.50
- ☐ 2.80
- ☐ 3.00
- ☐ 3.31
- ☐ 3.50
- ☐ 4.00
- ☐ 5.00
- ☐ 6.00
- ☐ 6.50
- ☐ 8.00
- ☐ 9.00
- ☐ 9.30
- ☐ 10.00

- ☐ 12.00
- ☐ 13.00
- ☐ 14.00
- ☐ 15.00
- ☐ 16.00
- ☐ 19.00
- ☐ 25.00
- ☐ 30.00
- ☐ 32.00
- ☐ 35.00
- ☐ 40.00
- ☐ 42.00
- ☐ 50.00
- ☐ 62.00
- ☐ 70.00
- ☐ 81.00
- ☐ 103.00
- ☐ AWG 12 + 12
- ☐ AWG 14 + 14 16 + 16
- ☐ AWG 20 + 20 18 + 18
- ☐ AWG 20 + 20 20 + 18
- ☐ AWG 20B
- ☐ AWG 22 + 22 20 + 22



Search → Clear

Maximum Cable Core Cross Section [mm2]



- ☐ 0.13
- ☐ 0.18
- ☐ 0.22
- ☐ 0.33
- ☐ 0.35
- ☐ 0.50
- ☐ 0.52
- ☐ 0.60
- ☐ 0.70
- ☐ 0.75
- ☐ 0.80
- ☐ 0.82
- ☐ 0.85
- ☐ 0.86
- ☐ 1.00
- ☐ 1.25
- ☐ 1.30
- ☐ 1.31
- ☐ 1.50
- ☐ 2.00
- ☐ 2.08
- ☐ 2.50
- ☐ 2.70
- ☐ 3.00
- ☐ 3.31
- ☐ 3.63
- ☐ 4.00
- ☐ 5.00
- ☐ 5.25
- ☐ 5.26
- ☐ 6.00
- ☐ 6.50
- ☐ 8.00
- ☐ 9.00
- ☐ 10.00
- ☐ 12.00
- ☐ 13.00
- ☐ 13.23
- ☐ 13.50
- ☐ 14.00
- ☐ 16.00
- ☐ 19.00
- ☐ 20.00
- ☐ 21.20
- ☐ 25.00
- ☐ 32.00
- ☐ 35.00
- ☐ 40.00
- ☐ 42.00
- ☐ 50.00
- ☐ 61.00

- ☐ 62.00
- ☐ 70.00
- ☐ 103.00
- ☐ AWG 12 + 12
- ☐ AWG 14 + 16
- ☐ AWG 18 + 18 16 + 16
- ☐ AWG 18B
- ☐ AWG 2
- ☐ AWG 20 + 20 18 + 18
- ☐ AWG 20 + 20 18 + 20



.

Minimum Cable Diameter [mm]



- ☐ 0.34
- ☐ 0.35
- ☐ 0.50
- ☐ 0.55
- ☐ 0.80
- ☐ 0.81
- ☐ 0.83
- ☐ 0.88
- ☐ 0.90
- ☐ 0.95
- ☐ 1.00
- ☐ 1.05
- ☐ 1.10
- ☐ 1.12
- ☐ 1.15
- ☐ 1.20
- ☐ 1.25
- ☐ 1.30
- ☐ 1.34
- ☐ 1.35
- ☐ 1.40
- ☐ 1.45
- ☐ 1.47
- ☐ 1.50
- ☐ 1.60
- ☐ 1.65
- ☐ 1.69
- ☐ 1.70
- ☐ 1.76
- ☐ 1.78
- ☐ 1.80
- ☐ 1.84
- ☐ 1.85
- ☐ 1.86
- ☐ 1.87
- ☐ 1.90
- ☐ 1.91
- ☐ 1.92
- ☐ 1.93
- ☐ 1.95
- ☐ 1.96
- ☐ 1.98
- ☐ 2.00
- ☐ 2.03
- ☐ 2.04
- ☐ 2.05
- ☐ 2.06
- ☐ 2.09
- ☐ 2.10
- ☐ 2.11
- ☐ 2.12
- ☐ 2.20
- ☐ 2.30
- ☐ 2.40
- ☐ 2.41
- ☐ 2.42
- ☐ 2.45
- ☐ 2.48
- ☐ 2.50
- ☐ 2.55
- ☐ 2.56
- ☐ 2.57
- ☐ 2.60
- ☐ 2.62

☐ 2.69  
☐ 2.70  
☐ 2.72  
☐ 2.80  
☐ 2.81  
☐ 2.84  
☐ 2.89  
☐ 2.94  
☐ 2.95  
☐ 2.97  
☐ 2.98  
☐ 3.00  
☐ 3.04  
☐ 3.05  
☐ 3.10  
☐ 3.11  
☐ 3.12  
☐ 3.13  
☐ 3.20  
☐ 3.30  
☐ 3.36  
☐ 3.40  
☐ 3.44  
☐ 3.45  
☐ 3.49  
☐ 3.53  
☐ 3.55  
☐ 3.61  
☐ 3.70  
☐ 3.74  
☐ 3.80  
☐ 3.81  
☐ 3.82  
☐ 3.87  
☐ 3.95  
☐ 3.97  
☐ 4.00  
☐ 4.06  
☐ 4.10  
☐ 4.30  
☐ 4.32  
☐ 4.40  
☐ 4.50  
☐ 4.52  
☐ 4.71  
☐ 4.95  
☐ 5.08  
☐ 5.20  
☐ 5.28  
☐ 5.50  
☐ 5.54  
☐ 5.80  
☐ 6.24  
☐ 6.31  
☐ 6.34  
☐ 6.40  
☐ 6.45  
☐ 6.50  
☐ 6.55  
☐ 6.60  
☐ 6.63  
☐ 7.00  
☐ 7.36  
☐ 7.40  
☐ 7.70  
☐ 7.75  
☐ 8.00  
☐ 8.01  
☐ 8.02  
☐ 8.47  
☐ 8.50  
☐ 8.54  
☐ 8.65  
☐ 8.69  
☐ 8.94  
☐ 9.00  
☐ 9.25  
☐ 9.30  
☐ 9.35  
☐ 9.40  
☐ 10.00  
☐ 10.04

- ☐ 10.34
- ☐ 10.40
- ☐ 10.41
- ☐ 10.50
- ☐ 10.84
- ☐ 10.90
- ☐ 11.00
- ☐ 11.10
- ☐ 11.39
- ☐ 11.93
- ☐ 11.94
- ☐ 12.00
- ☐ 12.10
- ☐ 12.16
- ☐ 12.50
- ☐ 12.75
- ☐ 13.00
- ☐ 13.20
- ☐ 13.97
- ☐ 14.30
- ☐ 15.00
- ☐ 15.20
- ☐ 15.30
- ☐ 17.00
- ☐ 18.97
- ☐ 19.79
- ☐ 20.00
- ☐ 31.10
- ☐ 32.00
- ☐ 50.00



Maximum Cable Diameter [mm]



- ☐ 0.50
- ☐ 0.62
- ☐ 0.75
- ☐ 0.80
- ☐ 0.85
- ☐ 1.00
- ☐ 1.01
- ☐ 1.05
- ☐ 1.10
- ☐ 1.20
- ☐ 1.30
- ☐ 1.40
- ☐ 1.45
- ☐ 1.50
- ☐ 1.60
- ☐ 1.65
- ☐ 1.70
- ☐ 1.75
- ☐ 1.80
- ☐ 1.83
- ☐ 1.85
- ☐ 1.86
- ☐ 1.87
- ☐ 1.88
- ☐ 1.90
- ☐ 1.92
- ☐ 1.93
- ☐ 2.00
- ☐ 2.02
- ☐ 2.03
- ☐ 2.04
- ☐ 2.05
- ☐ 2.06
- ☐ 2.08
- ☐ 2.10
- ☐ 2.12
- ☐ 2.13
- ☐ 2.19
- ☐ 2.20
- ☐ 2.25
- ☐ 2.30
- ☐ 2.34
- ☐ 2.35
- ☐ 2.40



☐ 2.41  
☐ 2.42  
☐ 2.45  
☐ 2.47  
☐ 2.48  
☐ 2.50  
☐ 2.51  
☐ 2.55  
☐ 2.60  
☐ 2.64  
☐ 2.65  
☐ 2.66  
☐ 2.68  
☐ 2.69  
☐ 2.70  
☐ 2.76  
☐ 2.77  
☐ 2.78  
☐ 2.80  
☐ 2.93  
☐ 3.00  
☐ 3.05  
☐ 3.10  
☐ 3.11  
☐ 3.12  
☐ 3.13  
☐ 3.15  
☐ 3.20  
☐ 3.25  
☐ 3.30  
☐ 3.31  
☐ 3.34  
☐ 3.35  
☐ 3.40  
☐ 3.49  
☐ 3.52  
☐ 3.56  
☐ 3.59  
☐ 3.60  
☐ 3.65  
☐ 3.67  
☐ 3.68  
☐ 3.70  
☐ 3.80  
☐ 3.89  
☐ 3.90  
☐ 3.94  
☐ 3.95  
☐ 3.96  
☐ 3.97  
☐ 4.00  
☐ 4.07  
☐ 4.09  
☐ 4.20  
☐ 4.21  
☐ 4.30  
☐ 4.40  
☐ 4.44  
☐ 4.48  
☐ 4.50  
☐ 4.53  
☐ 4.60  
☐ 4.67  
☐ 4.70  
☐ 4.80  
☐ 4.84  
☐ 5.00  
☐ 5.03  
☐ 5.08  
☐ 5.10  
☐ 5.24  
☐ 5.25  
☐ 5.28  
☐ 5.33  
☐ 5.35  
☐ 5.50  
☐ 5.54  
☐ 5.55  
☐ 5.60  
☐ 6.00  
☐ 6.10  
☐ 6.36

- ☐ 6.40
- ☐ 6.45
- ☐ 6.46
- ☐ 6.50
- ☐ 6.65
- ☐ 7.00
- ☐ 7.36
- ☐ 7.50
- ☐ 8.01
- ☐ 8.10
- ☐ 8.13
- ☐ 8.30
- ☐ 8.54
- ☐ 8.84
- ☐ 8.94
- ☐ 9.00
- ☐ 9.19
- ☐ 9.30
- ☐ 9.35
- ☐ 9.40
- ☐ 9.86
- ☐ 10.00
- ☐ 10.20
- ☐ 10.25
- ☐ 10.50
- ☐ 10.84
- ☐ 10.90
- ☐ 10.91
- ☐ 10.95
- ☐ 11.00
- ☐ 11.16
- ☐ 11.20
- ☐ 11.39
- ☐ 11.50
- ☐ 11.93
- ☐ 12.00
- ☐ 12.70
- ☐ 12.75
- ☐ 12.82
- ☐ 13.50
- ☐ 14.02
- ☐ 14.50
- ☐ 15.00
- ☐ 15.10
- ☐ 15.12
- ☐ 16.00
- ☐ 16.40
- ☐ 16.92
- ☐ 17.00
- ☐ 17.50
- ☐ 18.30
- ☐ 18.97
- ☐ 19.00
- ☐ 19.79
- ☐ 20.00
- ☐ 31.10
- ☐ 32.00
- ☐ 50.00
- ☐ 62.00





## DSQ 1.5 Female Sealed Tin Plating Tang Terminal Assembly, Cable Range 0.35 - 0.50 mm<sup>2</sup>

Part #15408850

[Question about this product?](#)



- Attributes
- Documents (2)

<b>Part #:</b>	15408850
<b>Description:</b>	DSQ 1.5 Female Sealed Tin Plating Tang Terminal Assembly, Cable Range 0.35 - 0.50 mm2
<b>Product Type:</b>	Terminal
<b>Status:</b>	 Active
<b>Blade size [mm]:</b>	1.5
<b>Terminal family:</b>	DSQ
<b>Series:</b>	1.5
<b>Gender:</b>	Female
<b>Sealed:</b>	Sealed
<b>Material:</b>	Various (Assembly)
<b>Plating:</b>	Tin
<b>Minimum Cable Core Cross Section [mm2]:</b>	0.35
<b>Maximum Cable Core Cross Section [mm2]:</b>	0.50
<b>Minimum Cable Diameter [mm]:</b>	1.20
<b>Maximum Cable Diameter [mm]:</b>	1.60
<b>Current range [A]:</b>	5
<b>Typical cable seal:</b>	15366022
<b>Weight [g]:</b>	0.35
<b>ELV compliant:</b>	 Yes
<b>RoHs compliant:</b>	 Yes

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.