

## Power Relay F

TE Internal #: 2-1393302-2

12VDC Coil Voltage Rating, 30 – 50A Contact Current Class,

Contact Arrangement 1 Form C SPDT-CO, Socket, Power Relay F,

Mini Relays

View on TE.com >



Relays & Contactors > Relays > Automotive Relays > Automotive Plug-In Relays > Mini Relays



Coil Voltage Rating: 12 VDC

Contact Current Class: 30 – 50 A

Contact Arrangement: 1 Form C SPDT-CO

Product Mount Type: Socket

Coil Resistance: 90 Ω

## **Features**

# **Configuration Features**

Contact Arrangement	1 Form C SPDT-CO
Electrical Characteristics	
Contact Limiting Short-Time Current	240 A
Contact Limiting Continuous Current	60 A
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Limiting Making Current	120 A
Insulation Initial Dielectric Between Contacts & Coil	500 Vrms
Contact Current Rating	60 A
Contact Limiting Breaking Current	60 A
Coil Power Rating DC	1.6 W
Contact Voltage Rating	12 VDC
Contact Switching Load (Min)	1000mA @ 5VDC
Coil Voltage Rating	12 VDC
Coil Resistance	90 Ω
Body Features	
Product Weight	35 g[1.2 oz]
Contact Features	

Silver Alloy

Contact Material



## **Termination Features**

Relay Connection Type	Plug-In
Terminal Configuration	Quick Connect Terminals
Mechanical Attachment	
Product Mount Type	Socket
Dimensions	
Product Width	25.9 mm[1.02 in]
Product Length	25.9 mm[1.02 in]
Product Height	24.9 mm[.98 in]
Usage Conditions	
Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Current Type	DC
Coil Magnetic System	Monostable
Other	
Environmental Ambient Temperature Class	105 – 125 °C
Length Class (Mechanical)	25 – 30 mm
Height Class (Mechanical)	20 – 25 mm
Width Class (Mechanical)	25 – 30 mm
Contact Current Class	30 – 50 A

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



#### Free

### Solder Process Capability

Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

# Compatible Parts



TE Part # 1-1904045-2 V23333Z1001A008-EV-100




V23333Z0001A007-EV-100



# Also in the Series | Power Relay F



Maxi Relays(12)



# Customers Also Bought




















TE Part #2-1393310-0 26A1348C=TERMINAL,CRMP,QC.250,

### **Documents**

**Product Drawings** 

V23134A0052C643-EV-CBOX

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-1393302-2\_S00F.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1393302-2\_S00F.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1393302-2\_S00F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

Power Relay F4, Mini ISO, Plug-In

English

**Product Specifications** 

**Definitions General Purpose Relays** 

English

12VDC Coil Voltage Rating, 30 – 50A Contact Current Class, Contact Arrangement 1 Form C SPDT-CO, Socket, Power Relay F, Mini Relays

