


SPECIFICATION CONTROL DRAWING




Product Revision		Product Dimensions				Cable Dimensions			
Product Name		Ident. Code	$L \pm 1.75$ ($L \pm 0.070$)	ϕA min	ϕB min	ϕD max	ϕE max	ϕF min	ϕG min
ST63-1-00	B	ST631R	16.50 (0.650)	1.90 (0.075)	2.65 (0.105)	1.90 (0.075)	2.65 (0.105)	0.90 (0.035)	0.50 (0.020)
ST63-2-00	B	ST632R	16.50 (0.650)	2.65 (0.105)	3.68 (0.145)	2.65 (0.105)	3.68 (0.145)	1.40 (0.055)	0.72 (0.030)
ST63-3-00	B	ST633R	16.50 (0.650)	4.30 (0.170)	5.08 (0.200)	4.30 (0.170)	5.08 (0.200)	2.15 (0.085)	1.25 (0.050)
ST63-4-00	B	ST634R	19.10 (0.750)	5.95 (0.235)	6.45 (0.255)	5.95 (0.235)	6.45 (0.255)	3.30 (0.130)	1.80 (0.070)
ST63-5-00	B	ST635R	19.10 (0.750)	7.00 (0.275)	7.60 (0.300)	7.00 (0.275)	7.60 (0.300)	4.30 (0.170)	2.50 (0.100)

MATERIALS

1. INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
2. SOLDER PREFORM WITH FLUX:
 - SOLDER: TYPE Sn63 per ANSI-J-STD-006.
 - FLUX: TYPE ROL1 per ANSI-J-STD-004.
3. MELTABLE RINGS: Stabilized thermoplastic. Color: blue.

APPLICATION

1. These parts are designed to provide an environment resistant shield terminations on cables, rated for 125°C minimum, meeting the dimensional criteria listed, having tin or silver plated shields and insulation.
2. When installed per Raychem process standard RCPS-100-70, assemblies will meet requirements of Raychem Specification RT-1404.
3. Temperature range: -55°C to +150°C.
4. For best results, prepare the cable as shown:



tyco Electronics		Raychem Products 305 Constitution Drive, Menlo Park, CA. 94025, USA		TITLE: SOLDERSLEEVE SHIELD TERMINATOR			
Unless otherwise specified dimensions are in millimeters. Inches dimensions are shown in brackets.				DOCUMENT NO.: ST63-X-00			
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	Tyco Electronics reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.		PROD. REV.: SEE TABLE	DOC. ISSUE: 6	DATE: 6-Dec-02	
PREPARED BY: mforonda		DCR NUMBER: D020557		REPLACES: D981346	SCALE: None	SIZE: A	SHEET: 1 of 1

If this document is printed it becomes uncontrolled. Check for the latest revision.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

[ST63-3-55-22-90](#) [ST63-5-55-22-5](#) [ST63-3-55-26-90](#) [041911-000](#) [ST63-2-55-22-90](#) [ST63-3-55-20-90](#) [ST63-3-55-24-90](#) [ST63-1-00](#) [ST63-2-55-20-90](#) [ST63-2-55-24-90](#) [ST63-5-00](#) [ST63-2-55-20-0](#) [ST63-3-55-24-6](#) [ST63-2-55-22-9](#) [ST63-3-55-24-9](#) [ST63-3-55-20-9](#) [ST63-1-55-24-9](#) [ST63-4-55-26-90](#) [ST63-4-55-22-9](#)